

TOWNSHIP 21 RANGE 04 POINT IDENTIFIER # 540300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 23 and 26

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Harvey Gordon and Charles T. Gardner, Deputy Surveyors, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 2 Page(s) 759)

Set 1/4 sec. post, from which
A Fir 10" dia., bears N.8°E., 45 lks. dist.
A Maple 8" dia., bears S.20°W., 52 lks. dist.

Gilbert A. Gardner - For: W.A. Woodard Lumber Co. - July/Dec. 1955 - C.S. File 42/131; C.S. 51/1-71 and M 2-16

Set a stake 4" x 4" x 3 ft. halfway between section corners, from which
14" D.Fir bears S.12 1/2°E., 10.0 ft. mkd. 1/4 S BT.
No other trees available.

Douglas Co. Surveyors Office - Milo Godfrey, Deputy - Nov. 1964 - C.S. File 42/131

Above renewal is based on fence cor. and set by proportion. If renewal visit to sec. cor. for 22, 23, 26 and 27 in "no good", neither is the above renewal.

Charles W. Guile - for: Les Chapman - Aug. 12, 1981 - M 88-64

Set 5/8" Iron rod at proportionate distances, from which
16" Fir scribed "1/4 S23 BT", bears N.8°45'W., 8.1 ft.
12" Fir scribed "1/4 S26 BT", bears S.12°55'W., 4.3 ft.

Donald Peel - For: Weyerhaeuser Co. - May 20, 1987 - M 104-28

CORNER REPORT ONLY
Found - 5/8" Rebar - 2" x 2" white post.
14" Fir bears S.13°W., 4.2 ft.
16" Fir bears N.10 3/4°W., 8.0 ft.
1/2" Iron pipe by Gardner, bears N.29°03'23"W., 81.26 ft.
(Note: Peel presumes 1/2" I.P. per Gardner, does not say on maps noted.)