

TOWNSHIP 21 RANGE 04 POINT IDENTIFIER # 600669

PRIMARY CORNER DESCRIPTION AP on line between Secs. 5 & 6

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Les Roberts - For: Ina Brooks - Nov. 1992 - M116-48

Set - 5/8"x30" Iron pins with Yellow plastic caps, cap mkd:
ROBERTS PLS 1039
12" Fir, N.55°E., 9.5' (scribed/painted red)
14" Fir, S.33°E., 6.8' (scribed/painted red)

BLM Dependent resurvey by Daniel N. Patterson, Cadastral
Surveyor, under Group No. 2335 surveyed July/Aug. 2010 -
(DCSO records Vol. 57 Page 22777 and Plat 2012-1, T21-4)

A point erroneously established as the N-N 1/64 sec. cor. of
secs. 5 and 6 by Roberts, PLS No. 1039, in 1992, and is
accepted as a point on line and now functions as a angle
point, monumented with an iron rod, 5/8" dia., firmly set,
projecting 2" above the ground, with yellow plastic cap mkd.
ROBERTS RLS 1039, from which the remains of bearing trees
mkd. by Roberts

A roothole bears N.55°E., 9.5 ft., with a decayed fir
trunk, 14" dia., tying alongside, with a healed blaze.

A roothole bears S.33°E., 6.8 ft., with a decayed fir
trunk, 16" dia., tying alongside, with a heated blaze.

At the corner point

Set a stainless steel post, 28" long, 2½" dia., 24" in the
ground, with brass cap mkd.

AP
S 6|S 5
2010

Deposit a magnet in a white plastic case at the base and iron
rod inside the stainless steel post.