

TOWNSHIP 21 RANGE 05 POINT IDENTIFIER # 100340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 19; & 24, T21-6

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Harvey Gordon and Charles T. Gardner, Deputy Surveyors, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 2 Page(s) 690)

Set ¼ sec. post, from which
A Fir 6" dia., bears N.79°W., 16 lks. dist.
A Fir 10" dia., bears S.45°E., 16 lks. dist.

GLO survey by W. P. Wright, U.S. Deputy Surveyor, under Contract #514, dated August 27, 1884 (DCSO records Vol. 2 Page(s) 698)

Found qr. sec. cor. standing.

Survey by Burton W. Holt - Wit: Ken Hebard - Feb. 24, 1960 - C.S. File 51/71-1

Determined by old BTs:
10" Fir S.45°E., 10.6 ft. which is now 31" with visible scribed.
6" Fir N.79°W., 10.6 ft. which is now a decayed stump with some scribe markings visible.
Set 1/2" x 36" iron pipe, from which
21" Fir bears S.79°W., 20.7 ft. mkd. ¼ S24 BT.
6" W. Red Cedar bears S.6°E., 34.4 ft. mkd. ¼ S19 BT.
Recent scribes on 36" Fir mkd. ¼S BT, bears N.7°W., 28.0 ft. from which a scribed stake bears S.23°W., 8.5 ft.
This stake and scribed tree do not refer to this actual corner.
Corner is approx. 200 ft. N. of small creek and 120 ft. S. of ridge top.

BLM Resurvey by Bryan S. Seibold, Cadastral Surveyor, under Group #1564, Surveyed Aug/Nov. 1990 - (DCSO records Vol. 50 Page(s) 19065)

The ¼ sec. cor., perpetuated by Holt in 1960, monumented with an iron pipe, ½" dia., firmly set, projecting 2" above ground, and a stone 12 x 8 x 8 ins., alongside, with the marks 1/4 S visible on the top, from which the remains of the original bearing trees:
A Fir stump 30" dia., bears S.49°E., 16 lks. dist., with scribe marks 1/4 S visible on opened blaze. (Rec. S.43°E.)
A root hole bears N.79°W., 16 lks. dist.
and bearing trees mkd. by Holt:
A Red Cedar 19" dia., bears S.7°E., 51 lks. dist., with healed blaze. (Cont. Next Page)

TOWNSHIP 21 RANGE 05 POINT IDENTIFIER # 100340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 19; & 24, T21-6

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A Fir 25" dia., bears S.80°W., 32 lks. dist., with healed double blaze and scribe marks ¼ S24 BT visible on a bark blaze.

and a bearing tree of which I have no record:

A Fir 45" dia., bears N.4°W., 44 lks. dist., with scribe marks ¼ S visible on a bark blaze.

At the corner point

Set an stainless steel post, 28" long, 2 1/2" dia., 25" in the ground, directly over the iron pipe, with brass cap mkd:

T 21 S
R6W R5W
1/4
S 24 | S 19
1990

Bury the marked stone alongside the stainless steel post.

Fd. OK by R. Ward, June 2001 - M138-26