

PRIMARY CORNER DESCRIPTION Sec. Cor. for 18 & 19; 13 & 24, T21-6

Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Harvey Gordon and Charles T. Gardner, Deputy Surveyors, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 2 Page(s) 690)

-----  
 Set post cor. of secs. 18, 19, 24 and 14; from which  
 A Cedar 24" dia., bears S.26°W., 19 lks. dist.  
 A Cedar 18" dia., bears S.32°E., 16 lks. dist.  
 A Maple 5" dia., bears N.52°W., 70 lks. dist.  
 A Hemlock 4" dia., bears N.71°E., 25 lks. dist.

GLO survey by W. P. Wright, U.S. Deputy Surveyor, under Contract #514, dated August 27, 1884 (DCSO records Vol. 2 Page(s) 698 and 826)

-----  
 (On page 826, Wright finds BTs as described above.)

(Page 698)

At place where old cor. to secs. 13, 24, 18 and 19 stood, the stumps of some of the witness trees found. Reestablished this corner by setting post, 6" dia., 4 ft. long in ground with mkd. stone 12", marked T21S S18 on NE.; R5W S19 on SE.; R6W S24 on SW.; S13 on NW. face; with 3 notches on N. & S. edges, from which

Cedar 27" dia., bears N.40°W., 75 lks. dist. mkd. T21S R6W S13 BT.  
 Cedar 14" dia., bears S.60°W., 50 lks. dist. mkd. T21S R6W S24 BT.  
 Maple 12" dia., bears S.42°E., 27 lks. dist. mkd. T21S R5W S19 BT.  
 Hemlock 8" dia., bears N.10°E., 45 lks. dist. mkd. T21S R5W S18 BT.

Douglas Co. Surveyors Office - Milo Godfrey, Deputy - V. Tracy; Clete Putnam, crew - Dec. 1961 - C.S. File 49/89-39

-----  
 Found - Cedar tree, now 30", S.60°W., 33.0 ft., previously opened, scribing "S24 T21S R6" visible on old face, tree nearly dead, whole inside, including face, rotting badly.

Cedar tree, down an dead, N.40°W., 49.5 ft., no scars or scribing found, one whole side burned away.

No trace of NE. or SE. bearing trees.

Set Brass cap at cor. mkd: County Surveyors Office

	T 21 S		
	S 13	S 18	
R6W	S 24	S 19	R5W
	1961		

(Cont. Next Page)

TOWNSHIP 21 RANGE 05 POINT IDENTIFIER # 100400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 18 & 19; 13 & 24, T21-6

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

New BTs- 13" D.Fir N.69½°E., 38.7 ft. mkd. T21S R5W S18 CS BT  
10" Hemlock S.11°E., 18.4 ft. mkd. T21S R5W S19 CSBT  
22" R.Cedar S.54°W., 57.0 ft. mkd. T21S R6W S24 CSBT  
52" D.Fir N.63°W., 31.0 ft. mkd. T21S R6W S13 CS BT.

Fd. OK by R. Ward, June 2001 - M138-26