

TOWNSHIP 21 RANGE 05 POINT IDENTIFIER # 100440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 18; & 13, T21-6

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Harvey Gordon and Charles T. Gardner, Deputy Surveyors, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 2 Page(s) 690)

-----  
Set ¼ sec. post, from which  
A Fir 20" dia., bears S.17°W., 34 lks. dist.  
A Fir 10" dia., bears S.19°E., 47 lks. dist.

GLO survey by W. P. Wright, U.S. Deputy Surveyor, under Contract #514, dated August 27, 1884 (DCSO records Vol. 2 Page(s) 698)

-----  
Old ¼ cor. gone. Set a post 4" dia., 4 ft. long, with marked stone, 12" in ground, mkd. ¼S on W. face, from which  
Fir 20" dia., bears S.19°E., 47 lks. dist. mkd. ¼ S BT.  
Fir 24" dia., bears S.17°W., 34 lks. dist. mkd. ¼ S BT.

Douglas Co. Surveyors Office - Milo E. Godfrey; V. Tracy and C. Putnam - May 1962 - C.S. File 49/143-27

-----  
Found - 33" D.Fir S.19°E., 31.0 ft., chopped open and found good scribing, portion of "S".  
42" D.Fir S.17°W., 22.4 ft., partially opened, previously, but not deep enough to expose scribing.

Set Brass cap at cor. mkd: County Surveyors Office  
T 21 S  
R6W S13 | S18 R5W  
1962

New BTs- 33" D.Fir S.19°E., 31.0 ft. mkd. ¼ S18 CS BT. (rescribed.)  
42" D.Fir S.17°W., 22.4 ft. mkd. ¼ S13 CS BT. (rescribed.)

Corner lies on W. slope of spur running S. from ridge top. Cor. approx. 60 ft. West of top of spur.

Fd. OK, July 1989 by D. Peel - M 109-55