

TOWNSHIP 21 RANGE 05 POINT IDENTIFIER # 140300

PRIMARY CORNER DESCRIPTION 1/4 cor. for Secs. 19 and 30

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by D. W. Applegate, under Contract #351, dated May 11, 1880 - (DCSO records Vol. 2 Page(s) 816)

Set ¼ sec. post, from which
A Fir 18" dia., bears N.88°E., 25 lks. dist.
A Fir 24" dia., bears S.63°W., 72 lks. dist.

Wilford N. Haines, #239 - For: John Woolley - 1955 - C.S. File 42/77 and M 12-32

Set Lot Marker by proportionate measurement.
Scribed- 12" D.Fir N.74°W., 2.7 ft.
18" D.Fir S.13°W., 5.3 ft.

Fd. OK, June 1965 - DCSO - C.S. File 49/68-48

BLM Resurvey by Bryan S. Seibold, Cadastral Surveyor, under Group #1564, Surveyed Aug/Nov. 1990 - (DCSO records Vol. 50 Page(s) 19054-55)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an stainless steel post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd: T 21 S R 5 W
1/4 $\frac{S 19}{S 30}$
1990

from which
A Fir 28" dia., bears S.39½°W., 29 lks. mkd. ¼ S30 BT.
A Fir 32" dia., bears N.34°W., 31½ lks. mkd. ¼ S19 BT.
Deposit white "DEEP-1" magnetic marker at base of stainless steel post.
From this point, a point established by Haines in 1955, bears S.3°50'30"W., 1.030 chs. dist., monumented with a T shaped iron rod, 1" dia., firmly set, projecting 5" above ground, with brass washer mkd. WILFORD N. HAINES 239 SURVEY POINT DRAIN, ORE., from which bearing trees mkd. by Haines:
A Fir 29" dia., bears S.12½°E., 9 lks., with healed blaze.
A Fir 17" dia., bears N.73¼°W., 5 lks., with healed blaze.
This point is not properly positioned and is not utilized in this survey.

Fd ok by G.Riley, 2/1998 - M128-26

Fd. BLM BC - 2, BTs & Haines "T" iron (68.09 ft. away) Set 6' steel post 0.5' south, by Harvey Christensen 5/2007 - M153-23