

TOWNSHIP 21 RANGE 05 POINT IDENTIFIER # 140400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 18 and 19

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W. P. Wright, U.S. Deputy Surveyor, under Contract #514, dated August 27, 1884 (DCSO records Vol. 2 Page(s) 827)

Set post 4" dia., 4 ft. long with mkd. stone 12" in the ground for $\frac{1}{4}$ sec. cor. mkd. $\frac{1}{4}$ S on N. face, from which
A Fir 10" dia., bears N.32°E., 36 lks. dist. mkd. $\frac{1}{4}$ S BT
A Cedar 20" dia., bears S.34°W., 16 lks. dist. mkd. $\frac{1}{4}$ S BT

Gilbert Gardner - For: Williamson Logging = Nov. 1954 - C.S. File 41/315

Found $\frac{1}{4}$ cor. Fd. 10" Fir now stump 24", lower part of "B" visible. Fd. 20" Cedar standing.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew July 30, 1970 - C.S. File 54/14-50

Found - Stumps of orig. BT, as follows:
10" Fir now 30" sawed stump, N.32°E., 23.8 ft., badly decayed, partial scribe marks "B" found.
At point for other orig. BT, there is a hole but no tree.

No trace of corner stone found.

Set Brass cap at cor. mkd: County Surveyors Office

T 21 S R 5 W

$\frac{1}{4}$ $\frac{S 18}{S 19}$

1970

New BTs- 24" Cedar S.66°W., 53.0 ft. mkd. $\frac{1}{4}$ S19 CS BT.

12" Cedar N.26°W., 26.8 ft. mkd. $\frac{1}{4}$ S18 CS BT.

From corner point, a 40" Cedar bears S.39°W., 21.5 ft. Has been chopped open, over 100 rings, nothing found.

Corner lies on NE. slope 50 ft. South and 75 ft. West of dry ravine, course SE., in dense undergrowth.

Fd. OK, July 10, 1989 by D. Peel - M 108-55

Fd. and used in BLM Resurvey by Bryan S. Seibold, Cadastral Surveyor, under Group #1564, Surveyed Aug/Nov. 1990 - (DCSO records Vol. 50 Page(s) 19064)