

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 7 and 18

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by W. P. Wright, U.S. Deputy Surveyor, under Contract #514, dated August 27, 1884 (DCSO records Vol. 2 Page(s) 829)

-----  
Set post 4" dia., 4 ft. long, with mkd. stone 12" in ground for ¼ sec. cor. mkd. ¼ S on N. face, from which  
A Hemlock 6" dia., bears S.8°W., 5 lks. dist. mkd. ¼ S BT  
A Hemlock 5" dia., bears N.36°W., 5 lks. dist. mkd. ¼ S BT

Gilbert Gardner - For: Weyerhaeuser Co. - 1956 and William Wilt, 1964 - C.S. file 62/63-19

-----  
(Robert Barta set this cor. under Gardner supervision. Corner was lost and the intention was to single proportion. Per Wilt in 1964, Barta found an error of 4 or 5 ft. in the proportioning. Therefore this point is only approx. The correction of the above error was not made at the cor. point according to Barta. A Fir stake and 2 BTs were scribed.)  
*See following corner report by the DCSO*

Douglas Co. Surveyors Office - June 23, 1989 - C.S. File 62/63-19

-----  
Found - A stone fd. by D. Peel measuring 6"x5"x12" long, 1 ft. below ground with smaller pieces of broken stone.

1" I.D. Alum. pipe protrudes 9" above ground, not of DCSO record. Alum. pipe set by William Wilt in 1964, marks ¼ cor. position proportioned by Gardner in an unrecorded survey dated 1956. This cor. is in Weyerhaeuser company survey file, it is noted as "not being an official corner."

From Stone, trees fd. by Don Peel:

14" dia. rotted 12 ft. high Hemlock snag, previously opened, no scribing or blazes fd., S.20°W., 4.4' 40" dia. down, with rotted out center Hemlock, no blazes or scribing fd., standing position approx., bears N.10°E., 7.0 ft.

1" I.D. Alum. pipe not of record, N.73°W., 63.8 ft.

From alum. pipe:

58" dia., D.Fir with a fully healed single blaze, bears N.24°W., 57.7 ft. (Rec. from W. Co. BT tag is S.24°E., 55.4 ft., face measurement.)

8" dia. D.Fir with fully healed double blaze, S.8°E., 29.2 ft. (Rec. from W. Co BT tag, N.8°W., 29.2 ft.)

No monument or new accessories established. Original calls do not fit well with positions noted. (Cont. Next Page)

TOWNSHIP 21 RANGE 05 POINT IDENTIFIER # 140500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 7 and 18

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Survey by Donald Peel - For: Weyerhaeuser - July 1989 - M  
108-55

-----

Set 2" x 42" Iron pipe with brass cap mkd. "T21S R5W 1/4 S7  
S18 PLS 752 1989". Set 6 ft. steel fence post 1 ft. West.  
New BTs- 11" Hemlock N.18°E., 5.9 ft. scribed ¼ S7 BT.  
27" Hemlock S.9°E., 21.6 ft. scribed ¼ S18 BT.  
1" alum. pipe bears N.81°26'52"W., 29.17 ft.