

TOWNSHIP 21 RANGE 05 POINT IDENTIFIER # 140600

PRIMARY CORNER DESCRIPTION 1/4 cor. for Secs. 6 and 7

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by W. P. Wright, U.S. Deputy Surveyor, under Contract #514, dated August 27, 1884 (DCSO records Vol. 2 Page(s) 832)

-----  
Set post 4" dia., 4 ft. long with mkd. stone 12" in ground for ¼ sec. cor. mkd. ¼ S on N. face, from which  
    An Alder 10" dia., bears S.26°E., 21 lks. dist. mkd. ¼ S BT.  
    An Alder 10" dia., bears N.39°E., 21 lks. dist. mkd. ¼ S BT.

-----  
Wilford N. Haines, #239 - For: Woolley Logging Co. - May 1957 - M 5-31

-----  
Found - 20" Alder N.39°E., 21 lks.  
Scribed- 30" Cedar S.08°30'W., 30.0 ft.  
Set Lot marker.

-----  
Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - 8/21/2001 - C.S. File 66/21-39

-----  
Found - 1957 Haines "T" Iron protruding 6" out of ground. 10" now 31" dia., Alder previously opened no scribing visible, bears N.39°E., 13.9 ft. (OBT)  
30" now 52" dia., Cedar with a fully healed blaze, bears S.8½°W., 30.0 ft. (1957)  
New - 14" dia., Hemlock double blazed & scribed "¼ S7 CS BT" bears S.64°W., 15.3 ft.  
10" dia., D.Fir double blazed & scribed "¼ S7 CS BT" bears S.64°E., 24.4 ft.  
Compass Decl. 17¾°E