

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 6; & 31, T20-5

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO Survey by Harvey Gordon, Deputy Surveyor, Under Contract #49, dated Oct. 17, 1854 - (DCSO records Vol. 2 Page(s) 786)

Set 1/4 sec. post, from which  
A R.Fir 15" dia., bears S.62°E., 125 lks. dist.  
A R.Fir 20" dia., bears N.24°W., 72 lks. dist.

Wilford N. Haines, #239 - For: Woolley Logging Co. - Oct. 1962 - M 24-30

No trace of original 1/4 corner found.  
Set 1" x 1" x 36" T. Iron, and scribed:  
18" D.Fir S.72°E., 27.5 ft.  
18" D.Fir N.36°W., 2.5 ft.

BLM Resurvey by Floyd A. Brooks and Timothy A. Kent, Cadastral Surveyors, under Group #648, Surveyed Aug. 1967/Sept. 1971 - (DCSO records Vol. 37 Page(s) 15265-66)

The 1/4 sec. cor., reestablished and recorded by Haines in 1962. This point is accepted as the best available evidence of the original corner position and is monumented with a "T" shaped iron rod, 36" long, 1" webs, firmly set, projecting 12" above ground, from which bearing trees mkd. by Haines:  
A Fir 17" dia., bears N.21°W., 5 1/2 lks., with healed blaze.  
A Fir 20" dia., bears S.74 1/2°E., 42 lks., with scribe marks  
1/4 S6 BT visible on open double blaze.

At the corner point  
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

T 20 S R 5 W  
1/4 S 31  
S 6  
T 21 S R 5 W  
1967

Deposit the "T" shaped iron rod alongside the iron post.

Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - 5/29/2002 - C.S. File 66/34-4

Found - No orig BTs found.  
1967 BLM BC/IP flush with ground. 1962 Haines "T" iron is along East edge of BC/IP protrudes 9" out of ground.  
18" now 20" dia., 6 ft. high D.Fir stump, tipped out of ground with a fully healed single blaze & BT tag center of root wad agrees well with 1967 rec. N.21°W., 3.6 ft. (1962)

continued next page

TOWNSHIP 21 RANGE 05 POINT IDENTIFIER # 140700

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 6; & 31, T20-5

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

18" now 33" dia., 2½ ft. high D.Fir stump we opened & find a curved scribe mark, bears S.74½°W., 27.7 ft. (1962)  
East - West blazed line and north edge of clear cut is 45 ft. North of BC/IP.  
Center line of E-W gravel logging road, 25 ft. north of BC/IP.

New - 16" dia., D.Fir double blazed & scribed "¼ S31 CS BT" bears N.38°W., 73.0 ft.  
5" dia., Alder double blazed & scribed "¼ S31 CS BT" bears N.20°E., 49.0 ft.  
20" dia., Hemlock double blazed & scribed "¼ S31 CS BT" bears N.84°E., 178.5 ft.

Note - No reasonable trees South (clear cut)  
Compass decl. 17½°E.

Fd. Ok by Craig Wanless, 8/2005 - M148-38