

TOWNSHIP 21 RANGE 05 POINT IDENTIFIER # 200100

PRIMARY CORNER DESCRIPTION Sec Cor 31 & 32; 5 & 6, T22-5

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 2 Page(s) 793)

-----  
Set post cor. of secs. 5, 6, 31 and 32, from which  
A Cedar 12" dia., bears S.75°W., 55 lks. dist.  
A Cedar 12" dia., bears S.70°E., 12 lks. dist.  
A Cedar 5" dia., bears N.15°W., 37 lks. dist.  
A Cedar 6" dia., bears N.53°E., 43 lks. dist.

O.F. Thiel - For: J.W. Dunbar; Levi Hunt; B.Ross - Feb. 1900 - Vol. 2 Pg 86 and also recorded in Vol. 2 Page 261

-----  
All original BTs been cut down but marks on 2 stumps still visible.

Set a post, from which  
A Cedar 10" dia., bears N.26°E., 44 lks. dist.  
A Cedar 16" dia., bears N.27°W., 200 lks. dist.  
A Maple 20" dia., bears S.26°W., 66 lks. dist.  
A Fir 28" dia., bears S.13°E., 87 lks. dist.

Searched for, not found, June 1965, B. Rogers, C.S. File 53/101-6

Not found, DCSO, V.Tracy, July 1970, C.S. File 54/14-14A

Survey by Donald Peel - For: Weyerhaeuser Co. - Feb. 1992 - M 114-60

-----  
Set by proportionate measurement  
A 2" x 41" Iron pipe with brass cap.  
BTs - 22" Cedar N.48°E., 24.4 ft., scribed T21S R5W S32 BT.  
26" Fir S.61°E., 19.7 ft. scribed T22S R5W S5 BT.  
8" Fir S.8°W., 38.4 ft. scribed T22S R5W S6 BT.  
11" Fir N.86°W., 13.1 ft. scribed T21S R5W S31 BT.

Fd. OK, Nov. 10, 1994, M 121-24  
Fd. Ok, by H. Christensen Jan. 1995, M 123-34