

TOWNSHIP 21 RANGE 05 POINT IDENTIFIER # 200340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for secs. 19 and 20

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W. P. Wright, U.S. Deputy Surveyor, under Contract #514, dated August 27, 1884 (DCSO records Vol. 2 Page(s) 824)

Set post 4" dia., 4 ft. long, with mkd. stone 12" in ground for ¼ sec. cor. mkd. ¼ S on W. face, from which
A Cedar 20" dia., bears N.37°W., 46 lks. dist. mkd. ¼ S BT
A Fir 6" dia., bears N.75°E., 38 lks. dist. mkd. ¼ S BT.

O.F. Thiel - For: Perkins and Bridges - March 19, 1903 - C.S. File 64/48 Pg. 15

No trace of old cor. or bearing trees.
Marked- Fir 12", N.59°E., 39 lks.
Fir 12", S.72°W., 29 lks.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew Aug/Sept. 1965 - C.S. File 54/14-16

Found - Orig. 6" now 26" Fir, N.75°E., 25.1 ft., open, shows scribe.
NW. BT, now turned out and out of position.
Set Brass cap at cor. mkd: County Surveyors Office
T 21 S R 5 W
¼ S 19 | S20
1965
New BTs- 17" D.Fir, S.52°W., 8.0 ft. mkd. ¼ S20 CS BT.
18" D.Fir, S.13°E., 13.7 ft. mkd. ¼ S20 CS BT.
This corner lies on hillside approx. 200 ft. N. of creek, flowing SE.

Fd. and Used in BLM Resurvey by Bryan S. Seibold, Cadastral Surveyor, under Group #1564, Surveyed Aug/Nov. 1990 - (DCSO records Vol. 50 Page(s) 19057)