

TOWNSHIP 21 RANGE 05 POINT IDENTIFIER # 200400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 17, 18, 19 and 20

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W. P. Wright, U.S. Deputy Surveyor, under Contract #514, dated August 27, 1884 (DCSO records Vol. 2 Page(s) 825)

Set post 6" dia., 4 ft. long, with mkd. stone, 12" in ground for cor. to secs. 17, 18, 19, and 20, mkd. T21S S17 on NE.; R5W S20 on SE.; S19 on SW.; and S18 on NW. faces, with 5 notches on E. and 3 on S. edge, from which

A Fir 40" dia., bears N.58°E., 19 lks. dist. mkd. T21S R5W S17 BT.

A Fir 36" dia., bears S.55°E., 66 lks. dist. mkd. T21S R5W S20 BT.

A Fir 24" dia., bears S.17°W., 41 lks. dist. mkd. T21S R5W S19 BT.

A Fir 26" dia., bears N.61°W., 80 lks. dist. mkd. T21S R5W S18 BT.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew Sept. 2, 1965 - C.S. File 54/14-15A

Looked for, not found.

Wilford N. Haines, #239 - March 15, 1968 - M 35-52

Found - 24" Fir S.17°W., 41 lks., down.

Stub for 36" Fir, S.55°E., 66 lks.

Stump hole for 40" Fir, N.72°E., not 59°E.

Set Iron pipe with brass cap, from which scribed new BTs:

16" Fir N.3°W., 15.8 ft.

20" Fir N.55°E., 29.1 ft.

18" Fir S.46°E., 23.7 ft.

20" Fir S.26°W., 4.2 ft.