

TOWNSHIP 21 RANGE 05 POINT IDENTIFIER # 200500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 7, 8, 17 and 18

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W. P. Wright, U.S. Deputy Surveyor, under Contract #514, dated August 27, 1884 (DCSO records Vol. 2 Page(s) 827-28)

Set post 6" dia., 4 ft. long with mkd. stone 12" in ground for cor. to secs. 7, 8, 17 and 18, mkd. T21S S8 on NE.; R5W S17 on SE.; S18 on SW.; S7 on NW. faces, with 4 notches on S. and 5 on W. edge, from which

A Dogwood 3" dia., bears N.77°E., 32 lks. dist. mkd. T21S R5W S8 BT.

A Fir 50" dia., bears S.37°E., 17 lks. dist. mkd. T21S R5W S17 BT.

A Fir 50" dia., bears S.47°W., 9 lks. dist. mkd. T21S R5W S18 BT.

A Laurel 7" dia., bears N.4°W., 24 lks. dist. mkd. T21S R5W S7 BT.

Wilford N. Haines, #239 - For: Harold Woolley - 1957 - M 7-66

Set Lot Marker.

Found - Stump and long butt 50" Fir, S.37°E., 17 lks.
Roots of 50" Fir S.47°W., 9 lks.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - Vernon Tracy; Clete Putnam, crew - Feb. 20, 1962 - C.S. File 49/89-47

Corner Report Only

Found, not substantiated by Surveyor Office.

Found Haines T. Iron and cap.

Found Haines bearing trees, not recorded:

6" Fir S.41°W., 3.0 ft. scribing visible in partly covered scar.

9" Fir S.56°E., 45.5 ft. scribing visible in partly covered scar.

40" Fir N.28°W., 49.2 ft. bark scribed "T21S R5W S7 BT 363".

This corner renewal by Haines is recorded but his witness trees are not.

Fd. OK, Dec. 1964 by DCSO

Fd. OK, July 1989 by D. Peel - M 108-55

Harvey Christensen - 9/2000 (Filed 5/22/2008) - C.S. File 65/63-20

Found - ¾"x¾" "T" post w/1" brass plate "HAINES 239" facing west, .3' above grade. continued next page

TOWNSHIP 21 RANGE 05 POINT IDENTIFIER # 200500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 7, 8, 17 and 18

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

<p>18" W.Hemlock (Fir) S.28°W., 4.6, healed face. 39" D.Fir, N.22°W., 49.6, healed face. 21" D.Fir, S.54°E., 46.1, healed face. 7" R.Alder, N.83°E., 19.7, barked scribed "T21S R5W S8 BT" Set - 5' steel post 1' west. All distances to side center (nail) of new BTs.</p>
<p>Fd as per record June 2018 - D. Edwards - C.S. File 65/98-7</p>