

TOWNSHIP 21 RANGE 05 POINT IDENTIFIER # 200540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 7 and 8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by W. P. Wright, U.S. Deputy Surveyor, under Contract #514, dated August 27, 1884 (DCSO records Vol. 2 Page(s) 830)

Set post 4" dia., 4 ft. long with mkd. stone 12" in ground for ¼ sec. cor. mkd. ¼ S on W. face, from which
A Hemlock 12" dia., bears N.47°W., 36 lks. dist. mkd. ¼ S
BT
A Hemlock 6" dia., bears S.50°E., 7 lks. dist. mkd. ¼ S BT

Wilford N. Haines, #239 - For: Harold Woolley - 1957 (Filed Jan. 1958) - M 7-66

Set Lot Marker.
Scribed- 10" Hemlock N.09°E., 34.6 ft.
10" Alder N.17°W., 29.9 ft.

Wilford N. Haines, #239 - For: Feb. 1962 - C.S. File 51/234-4

Found T Iron set in 1957. All BTs have been knocked down and burned. Found Alder N.17°W., 29.7 ft.
New BTs- 26" Fir N.1°W., 146.0 ft.
16" Fir N.19°E., 185.8 ft.

David Edwards - For: Seneca Jones Timber Co. - June 2018 - C.S. File 65/98-7

Found - Haines "T" iron
A 24" dia. Fir w/H.B. bears N.19°E., 185.8'
A 40" dia. Fir W/H.B. bears N.1°W., 146.0'
A six foot steel post is set 2 ft north.