

PRIMARY CORNER DESCRIPTION Sec. Cor. for 5, 6, 7 and 8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W. P. Wright, U.S. Deputy Surveyor, under Contract #514, dated August 27, 1884 (DCSO records Vol. 2 Page(s) 830)

Set post 6" dia., 4 ft. long, with mkd. stone in ground for cor. to sec. 5, 6, 7 and 8, mkd. T21S S5 on NE.; R5W S8 on SE.; S7 on SW.; S6 on NW. face, with 5 notches on S. and E. edges, from which
A Fir 48" dia., bears S.72°W., 25 lks. dist. mkd. T21S R5W S7 BT.
A Fir 20" dia., bears N.34°W., 65 lks. dist. mkd. T21S R5W S6 BT.
A Fir 24" dia., bears N.49°E., 51 lks. dist. mkd. T21S R5W S5 BT.
A Dogwood 7" dia., bears S.85°E., 40 lks. dist. mkd. T21S R5W S8 BT.

Wilford N. Haines, #239 - For: Woolley Logging Co. - May 1957 - M 5-31

Found - 36" Fir stump N.49°E., 65 lks.
10" Dogwood S.85°E., 40 lks.
Scribed- 10" Fir S.85°E., 25.3 ft.

Wilford N. Haines, #239 - For: Harold Woolley - 1957 (Filed Jan. 1958) - M 7-66

Found - Lot Marker.
36" Fir stump N.49°E., 65 lks.
10" Dogwood S.85°E., 40 lks.
10" Fir S.85°E., 25.3 ft.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew Aug/Sept. 1965 - C.S. File 54/14-8

Found - T Iron and scribed post.
Orig. BT gone, 20" Fir N.34°W., 42.9 ft.
48" Fir stump, no scribing visible, S.72°W., 16.5 ft
24" Fir now 30" N.49°E., 33.7 ft. scribed T21S R5W S5 CS BT.
New BTs- 12" Hemlock N.23°E., 44.3 ft. scribed T21S R5W S5 CS BT.
18" Hemlock N.14°W., 65.1 ft. mkd. T21S R5W S6 CS BT
14" D.Fir S.31°W., 72.3 ft. mkd. T21S R5W S7 CS BT.

Fd. OK, Dec. 1994 by L. Roberts - M 121-30

Continued next page

TOWNSHIP 21 RANGE 05 POINT IDENTIFIER # 200600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 5, 6, 7 and 8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

David Edwards - For: Seneca Jones Timber Co. - June 2018 -
C.S. File 65/98-7

Found - Haines "T" iron
 A 25" dia. Hemlock w/H.B. brs. N.24°E., 44.2'
 A 36" dia. Fir stump bears N.49°E., 34.0'
 A 28" dia. Fir w/H.B. bears S.85°E., 24.5'
New BT - A 12" dia. Fir bears N.38°W., 29.0'
 All other BTs per (record) are gone.
 A six foot steel post is set 2 feet south.