

TOWNSHIP 21 RANGE 05 POINT IDENTIFIER # 200640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 5 and 6

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W. P. Wright, U.S. Deputy Surveyor, under Contract #514, dated August 27, 1884 (DCSO records Vol. 2 Page(s) 833)

Set post 4" dia., 4 ft. long, with mkd. stone 12" in ground for 1/4 sec. cor. mkd. 1/4 S on W. face, from which
A Fir 16" dia., bears N.89°E., 66 lks. dist. mkd. 1/4 S BT
A Fir 12" dia., bears N.62°W., 84 lks. dist. mkd. 1/4 S BT

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - Vernon Tracy; Clete Putnam, crew - March 1962 - C.S. File 49/89-48

Found - Old Fir stump 30", N.89°E., 43. ft., opened previously, good scribing "BT 1/4S" visible on old face.

No trace found of NW. BT.

Set Brass cap at cor. mkd: County Surveyors Office
T 21 S R 5 W
1/4 S6|S5
1962

New BTs- 24" D.Fir N.79°E., 40.7 ft. mkd. 1/4 S5 CS BT.
5" D.Fir N.66°W., 53.1 ft. mkd. 1/4 S6 CS BT.

Fd. OK, Dec. 1994 by L. Roberts - M 121-30