

TOWNSHIP 21 RANGE 05 POINT IDENTIFIER # 240400

PRIMARY CORNER DESCRIPTION 1/4 cor. for Secs. 17 and 20

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W. P. Wright, U.S. Deputy Surveyor, under Contract #514, dated August 27, 1884 (DCSO records Vol. 2 Page(s) 826)

-----  
Set post 4" dia., 4 ft. long, with mkd. stone 12" in ground for ¼ sec. cor. mkd. ¼ S on N. face, from which  
A Fir 20" dia., bears N.30°E., 54 lks. dist. mkd. ¼ S BT  
A Fir 36" dia., bears S.64°E., 20 lks. dist. mkd. ¼ S BT

Wilford N. Haines, #239 - For: Woolley Logging Co. - Feb. 20, 1962 - M 23-34

-----  
Set 1" x 1" x 36" T Iron from original BTs.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew Aug/Sept. 1965 - C.S. File 54/14-13

-----  
Found - Haines T Iron  
Orig. 20" now 50" Fir N.30°E., 35.6 ft., shows BT ¼ S. Bark scribe appears to be very old. This BT has another tree leaning into it.  
Orig. 36" now 58" Fir S.64°E., 13.2 ft., found possible bark scribe. This BT injured and bark is burned.  
Due to the size and condition of orig. BTs., we mark  
New BTs- 8" D.Fir S.80°E., 32.1 ft. mkd. ¼ S20 CS BT.  
15" D.Fir N.28°W., 28.5 ft. mkd. ¼ S17 CS BT.  
This corner lies on N. side of ravine, course N.70°W.