

TOWNSHIP 21 RANGE 05 POINT IDENTIFIER # 240500

PRIMARY CORNER DESCRIPTION 1/4 cor. for Secs. 8 and 17

Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____

GLO survey by W. P. Wright, U.S. Deputy Surveyor, under Contract #514, dated August 27, 1884 (DCSO records Vol. 2 Page(s) 828)

Set post 4" dia., 4 ft. long, with mkd. stone 12" in ground for 1/4 sec. cor. mkd. 1/4 S on N. face, from which
A Maple 5" dia., bears S.16°E., 29 lks. dist. mkd. 1/4 S BT
A Maple 4" dia., bears N.22°E., 43 lks. dist. mkd. 1/4 S BT

Wilford N. Haines, #239 - For: Harold Woolley - 1957 - M 7-66

Set Lot Marker.
Scribed- 16" Fir S.31 1/2°W., 15.0 ft.
8" Maple N.33°W., 23.9 ft., slope.

Harvey Christensen - 9/2000 (Filed 5/22/2008) - C.S. File 65/63-18

Found - "T" post, bent out of position.
16" BL Maple, N.33°W., 23.9 (slope), healed face.
30" D.Fir, S.3.5°W., 15.0, blow down, over "T"
Accessories - 16" B.L. Maple, N.29°W., 19.5, healed face.
5" D.Fir, N.78°W. (diagram shows it drawn in the NE quad) 36.1, blazed & scribed "X" "BT"
30" D.Fir S.3.5°E., 24.2, blazed & scribed "1/4 S17"
20" W.Hemlock, S.50°W., 18.5, blazed & scribed "1/4 S17"
Set - Reset corner with 5/8"x30" rebar w/YPC "NTCI LS 2603" using "T" post hole & Maple BT. Set monument with 1' rock mound around. Corner lays 1' north of draw. Set 5' steel post 1' East.