

TOWNSHIP 21 RANGE 05 POINT IDENTIFIER # 300200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 28, 29, 32 and 33

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Harvey Gordon and Charles T. Gardner, Deputy Surveyors, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 2 Page(s) 809)

Set post cor. of secs. 28, 29, 32 and 33, from which
A Dogwood 6" dia., bears S.36°E., 82 lks. dist.
A Redwood 6" dia., bears S.55°W., 110 lks. dist.
A Fir 35" dia., bears N.63°E., 53 lks. dist.
A Fir 32" dia., bears N.84°W., 94 lks. dist.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - Vernon Tracy; Clete Putnam, crew - April 1962 - C.S. File 49/89-56

Found - 60" Fir N.63°E., 35.0 ft., old bark scribing visible
"T 2 R"
56" Fir N.84°W., 62.0 ft., old bark scribing visible
"S29 T21S R5W"
28" I.Cedar S.55°W., 72.6 ft., shows two faint scars.
Did not find SE. BT.

Corner falls in bottom of deep gully.
Set Brass cap 20 ft. North of cor. for Wit. Cor. mkd:

County Surveyors Office
T 21 S R 5 W
W.C. 20' S.
to cor.
S 29 | S 28
D 32 | S 33
1962

New BTs- 9" W.Fir S.65°W., 20.6 ft. mkd. T21S R5W S32 CS WC BT.
6" I.Cedar N.71°W., 38.2 ft. mkd. T21S R5W S32 CS WC BT.
16" R.Cedar N.48°E., 47.3 ft. mkd. T21S R5W S28 CS WC BT.
18" D.Fir S.56°E., 62.0ft. mkd. T21S F5W S33 CS WC BT.

BLM resurvey by Wayne L. Rogers, Cadastral Surveyor, Group #1059, surveyed April/Dec. 1981 - (DCSO records Vol. 45 Page(s) 17316-17)

The Sec. Cor. perpetuated by person(s) unknown, monumented with an iron rod, 1/2" dia., firmly set, projecting 6" above ground, from which the remaining original bearing trees:
(Cont. Next Page)

TOWNSHIP 21 RANGE 05 POINT IDENTIFIER # 300200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 28, 29, 32 and 33

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

A Fir 65" dia., bears N.63°E., 53 lks. dist., with fragmentary scribe marks visible on bark blaze.

A Cedar 34" dia., bears S.50½°W., 102 lks. dist., with healed blaze. (Rec. S.55°W., 110 lks.)

A Fir 60" dia., bears N.88°W., 86 lks. dist. with scribe marks S29 T21S R5 visible on bark blaze. (Rec. N.84°W., 94 lks.)

At the corner point

Set an alum. post 28" long, 2½" dia., 24" in the ground, directly over the iron rod, with alum. cap mkd.

T 21 S R 5 W
S 29 | S 28
S 32 | S 33
1981

from which a new bearing tree

A Grand Fir 16" dia., bears S.6¼°E., 55 lks. dist., mkd. T21S R5W S33 BT.

From this point, a witness corner established by Godfrey in 1962, bears North, 0.303 chs. dist., monumented with an iron post, 1¼" dia., firmly set, projecting 12" above ground with brass cap mkd. in 1962, from which bearing trees mkd. by Godfrey:

A Cedar 26" dia., bears N.47°E., 72 lks. dist., with healed double blaze.

A Fir 24" dia., bears S.58°E., 93 lks. dist., with healed double blaze.

A Grand Fir 16" dia., bears S.62½°W., 31 lks. dist., with healed blaze.

A Cedar 8" dia., bears N.73¼°W., 57 lks. dist., with healed blaze.

Fd. OK, Feb. 1994 by C. Mulkins and/or H. Christenson - M 118-63

Found OK by R. Ward, Oct. 2001 - M139-23

Ron Rice, Ward NW, Inc. - For: Seneca Jones Timber Co. 8/2006 - M151-24

Found - WC 2½" County Surveyors Office brass cap dated 1962 bears north 20.9' - record 20.0'
26" Grand Fir bears S.6¼°E., 36.3' - healed face
65" D.Fir bears N.63°E., 35.0' - faint bark scribing
38" I.Cedar bears S.50½°E., 67.3' - healed face
All BTs have red painted band and face plus BT tag.
Galvanized post set adjacent to corner monument.