

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 20 and 21

Alias	Description

GLO survey by Harvey Gordon and Charles T. Gardner, Deputy Surveyors, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 2 Page(s) 811)

Set ¼ sec. post, from which
A Fir 22" dia., bears N.73°W., 24 lks. dist.
A Fir 36" dia., bears N.53°E., 44 lks. dist.

Wilford N. Haines, #239 - For: Woolley Logging Co. - Feb. 20, 1962 - M 23-34

Found - 22" Fir N.73°W., 24 lks., now about 36", rescribed on S. side.
Set 1" x 1" x 36" T. Iron and
Scribed- 50" Fir N.21°E., 16.5 ft.
36" Fir N.53°E., 44 lks., down.

Cor. OK, June 1965 - DCSO C.S. File 53/101-20

BLM dependent resurvey by Wayne Rogers & Bryan Seibold Cadastral Surveyors & Robert Browning, Surveying Technician, under Group #1814, surveyed Aug. 1996/April 1998 - (DCSO rec. Vol. 53 Page(s) 20412)

The ¼ sec. cor. of secs. 20 & 21, perpetuated by Haines, in 1962, monumented with a "T" iron, 1x1", firmly set, projecting 6" above ground, from which the remains of an OBT
A sawed fir stump, 42" dia., bears N.73°W., 24 lks., no marks visible.

and a bearing tree mkd. by Haines
A fir, 58" diam., bears N.21°E., 23 lks., with scribe marks ¼ S21 BT visible on a bark blaze.

At the corner point
Set a stainless steel post, 28" long, 2½" dia., 28" in the ground, directly over the "T" iron, with brass cap mkd.

T21S R5W
¼
S 20|S 21
1996

from which a new bearing tree
A maple, 10" diam., bears N.78°W., 74 lks., mkd. ¼ S20 BT.
Deposit a magnet in a white plastic case at the base of the stainless steel post.

continued next page

TOWNSHIP 21 RANGE 05 POINT IDENTIFIER # 300340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 20 and 21

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Harvey Christensen, For: Guistina Land & Timber and Thomas Mulder - Sept. 1999 - M 133-32

Found - 3.25" 1996 BLM flush with ground.
59" D.Fir N.22.5°E., 15.4 ft. bark scribed /w Haines washer @ center.
42" D.Fir N.73°W., 15.8 ft. stump - set rail spike @ center.
11" BL. Maple N.78°W., 49.1 ft. scribing visible.
7" W.Cedar S.85°E., 17.4 ft. blazed & scribed "¼ S21 BT"