

PRIMARY CORNER DESCRIPTION Sec. Cor. for 16, 17, 20 and 21

Alias	Description
Alias	Description
Alias	Description
Alias	Description

<p>GLO survey by Harvey Gordon and Charles T. Gardner, Deputy Surveyors, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 2 Page(s) 811)</p> <p>-----</p> <p>Set post cor. of secs. 16, 17, 20 and 21, from which</p> <ul style="list-style-type: none">A Fir 70" dia., bears N.70°W., 38 lks. dist.A Fir 15" dia., bears N.66°E., 27 lks. dist.A Fir 60" dia., bears S.33°W., 10 lks. dist.A Fir 12" dia., bears S.32°E., 33 lks. dist.
<p>Fd. & Used in GLO survey by W P Wright, U.S. Deputy Surveyor, under Contract #514, dated August 27, 1884 (DCSO rec Vol. 2 Pg 825)</p>
<p>SE & SW BTs standing Oscar Thiel - 1942 - FB 117 Pg 27 (added 6/11/2012)</p>
<p>Wilford Haines - For: Woolley Logging - Feb 20, 1962 - M23-34</p> <p>-----</p> <p>Found - 12" Fir S.32°W., 33 lks., now 42", rescribe on East side.</p> <ul style="list-style-type: none">60" Fir S.33°E., 10 lks., now 62", rescribe on West side. <p>Hole for 70" Fir N.70°W., 38 lks.</p> <p>Set 1" x 1" x 36" T Iron for corner.</p>
<p>Douglas County Surveyors Office - Vernon "Ray" Tracy and crew Aug/Sept. 1965 - C.S. File 54/14-7</p> <p>-----</p> <p>Found - Haines T Iron.</p> <ul style="list-style-type: none">Orig. 60" now 62" Fir S.33°E., 6.6 ft., recorded as S.33°W., shows faint orig. bark scribe "T21 R5W S21B", rescribe "T21S R5W S21".Orig. 12" now 42" Fir S.32°W., 21.8 ft. recorded as S.32°E., shows scar. Do not open. <p>New BT - 9" Laurel N.78°W., 29.8 ft. mkd. T21S R5W S17 CS BT.</p> <p>No tree available to NE.</p> <p>This corner lies on South side, top of ridge, running NW & SE</p>
<p>BLM dependent resurvey by Wayne Rogers & Bryan Seibold Cadastral Surveyors & Robert Browning, Surveying Technician, under Group #1814, surveyed Aug. 1996/April 1998 - (DCSO rec. Vol. 53 Page(s) 20413-4)</p> <p>-----</p> <p>The cor. of secs. 16, 17, 20 & 21, perpetuated by Haines, in 1962, further perpetuated by Tracy, in 1965, monumented with a "T" iron, 1x1", firmly set, projecting 10" above ground, from which the remains of the original bearing trees <u>CONT</u></p>

TOWNSHIP 21 RANGE 05 POINT IDENTIFIER # 300400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 16, 17, 20 and 21

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A fir, 61" diam., bears S.32°E., 10 lks., with fragmentary scribe marks visible on a bark blaze.
A sawed fir stump, 48" diam., bears S.33°W., 33 lks., with scar visible on top of stump. (Record S.31°W.)
and a bearing tree mkd. by Tracy
A madrone, 11" dia. bears N.78°W., 45 lks. with healed double blazes.
At the corner point
Set a stainless steel post, 28" long, 2½" diam., 25" in the ground, directly over the "T" iron, with brass cap mkd.
T21S R5W
S 17 | S 16
S 20 | S 21
1996
from which a new bearing tree
A fir, 12" dia. bears N.22°E. 75 lks. mkd. T21S R5W S16 BT
No suitable accessory available in the SW. quadrant.
Deposit a magnet in a white plastic case at the base of the stainless steel post.