

TOWNSHIP 21 RANGE 05 POINT IDENTIFIER # 300500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 8, 9, 16 and 17

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Harvey Gordon and Charles T. Gardner, Deputy Surveyors, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 2 Page(s) 812)

Set post cor. of secs. 8, 9, 16 and 17, from which
A Fir 18" dia., bears S.17°W., 61 lks. dist.
A Fir 8" dia., bears N.40°E., 20 lks. dist.
A Hemlock 15" dia., bears S.46°E., 35 lks. dist.
A Cedar 10" dia., bears N.30°W., 47 lks. dist.

Cor. Fd. and used in GLO survey by W. P. Wright, U.S. Deputy Surveyor, under Contract #514, dated August 27, 1884 (DCSO records Vol. 2 Page(s) 821)

Wilford N. Haines, #239 - For: Harold Woolley - 1957 (filed Jan. 1958) - M 7-66

Found - Stump BT, S.17°W., 61 lks.
Scribed- 36" Fir N.17°W., 40.5 ft.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew Aug/Sept. 1965 - C.S. File 54/14-12

Found - Haines T Iron at corner and BTs as recorded.
36" D.Fir N.17°W., 40.5 ft., shows "T21S R5W S8 BT", bark scribe and Haines' button on face.
Orig. 18" now 48" Fir stump S.17°W., 40.3 ft., no scribe visible on open face. Open higher on stump and find "S17" scribe.
No trace of other orig. BT.
New BTs- 7" D.Fir N.47°E., 7.4 ft. mkd. T21S R5W S9 CS BT.
8" D.Fir S.86°E., 19.5 ft. mkd. T21S R5W S16 CS BT.
7" D.Fir S.32°W., 14.1 ft. mkd. T21S R5W S17 CS BT.

Harvey Christensen - 9/2000 (Filed 5/22/2008) - C.S. 65/63-17

Found - ¾"x¾" "T" post, w/1" brass plate "HAINES 236 (239)" .6' above grade.
Accessories - 7" D.Fir, N.47°E., 7.4, healed face (twin)
16" D.Fir, S.86°E., 19.5, healed face.
9" D.Fir, S.32°W., 14.7, healed face.
42" D.Fir, N.17°W., 40.5, bark scribing visible, stump.
9" D.Fir, N.52°W., 31.9, blazed & scribed "T21S R5W S8 BT"
Monument located + 200' West of gravel road "SAND RIDGE ROAD". Distances to side center (nail of new BTs).