

TOWNSHIP 21 RANGE 05 POINT IDENTIFIER # 300600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 4, 5, 8 and 9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W. P. Wright, U.S. Deputy Surveyor, under Contract #514, dated August 27, 1884 (DCSO records Vol. 2 Page(s) 822)

Set post 6" dia., 4 ft. long with mkd. stone 12" in ground for cor. to secs. 4, 5, 8 and 9 mkd. T21S S4 on NE.; R5W S9 on SE.; S8 on SW.; S5 on NW. faces, from which
A Fir 14" dia., bears N.47°E., 28 lks. dist. mkd. T21S R5W S4 BT.
A Fir 14" dia., bears S.65°E., 33 lks. dist. mkd. T21S R5W S9 BT.
A Fir 12" dia., bears S.41°W., 28 lks. dist. mkd. T21S R5W S8 BT.
A Fir 40" dia., bears N.20°W., 50 lks. dist. mkd. T21S R5W S5 BT.

Wilford N. Haines, #239 - For: Harold Woolley - 1957 (Filed Jan. 1958) - M 7-66

Set Lot Marker. Found all old BTs down.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew Aug/Sept 1965 - C.S. File 54/14-5

Found - Haines T Iron at corner.
Find real old scribed stake at corner.
Orig. 40" now 60" down Fir, face down, N.20°W., 33.0 ft.
NE. and SE. original BTs, down and rotted.
Orig. 12" now 32" Fir S.34°W., 18.5 ft., shows axe marks, scribe marks on chip nailed to tree.
New BTs- 9" Hemlock bears N.16°E., 7.0 ft. scribed S4 T21S R5W CS BT.
7" Hemlock bears S.9°E., 13.9 ft. scribed S9 T21S R5W CS BT.
11" Hemlock bears N.35°E., 15.9 ft. scribed S5 T21S R5W CS BT.
Rescribe now 32" Fir S.34°W., 18.5 ft. scribed S8 T21S R5W CS BT.

Fd. OK, Dec. 1994 by L. Roberts - M 121-30