

TOWNSHIP 21 RANGE 05 POINT IDENTIFIER # 300640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 4 & 5

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W. P. Wright, U.S. Deputy Surveyor, under Contract #514, dated August 27, 1884 (DCSO records Vol. 2 Page(s) 824)

Set post 4" dia., 4 ft. long with mkd. stone 12" in ground for 1/4 sec.cor. mkd. 1/4 S on W. face, from which
A Chinquapin Oak, 6" dia., bears S.28°E., 21 lks. dist. mkd. 1/4 S BT.
A Fir 20" dia., bears N.75°W., 3 lks. dist. mkd. 1/4 S BT

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew Aug. 16, 1965 - C.S. File 54/14-15A

Looked for, not found.

Douglas Co. Surveyors Office - Randall Smith and Stephen Flause, crew - March 31, 1994 - C.S. File 64/51-2

Found - Nail set by Les Roberts. (No source given)
20" now down and rotting D.Fir of indeterminable size, with scribing found "S 1/4 BT" bears N.75°W., 2.0 ft. (agrees w/orig. record and Roberts survey)

Orig. SE. BT not found.

Set 2 3/8" dia. DCSO brass cap on a 1 3/8" x 32" long iron pipe is set at referenced position of nail. BC/IP protrudes 5" above ground, cap stamped: Douglas County Surveyors

T 21 S R 5 W
1/4
S 5 | S 4
1994
Office

New BTs- 8" dia. D.Fir, double blazed and scribed "1/4 S4 CS BT", bears N.6 1/2°E., 12.8 ft.

12" dia. D.Fir, double blazed and scribed "1/4 S4 CS BT", bears S.71°E., 10.9 ft.

15" dia. D.Fir, double blazed and scribed "1/4 S5 CS BT", bears S.29 1/2°W., 10.6 ft.

12" dia. D.Fir, double blazed and scribed "1/4 S5 CS BT" bears N.83°W., 13.5 ft.

Sketch in file.

Corner lies on top of a N-S ridge approx. 100 ft. West of a dirt road.