

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Harvey Gordon, Deputy Surveyor, Under Contract #49, dated Oct. 17, 1854 - (DCSO records Vol. 2 Page(s) 785)

 Set post cor. of secs. 4, 5, 32 and 33, from which
 A R.Fir 10" dia., bears N.50°W., 64 lks. dist.
 A R.Fir 8" dia., bears S.71°W., 65 lks. dist.
 A R.Fir 20" dia., bears S.55°E., 34 lks. dist.
 A R.Fir 40" dia., bears N.75°E., 121 lks. dist.

Fd. and used cor. in GLO survey by W. P. Wright, U.S. Deputy Surveyor, under Contract #514, dated August 27, 1884 (DCSO records Vol. 2 Page(s) 823)

Douglas Co. Surveyors Office - Bruce Rogers, Deputy, Mike Stone crew - June 1965 - C.S. File 53/101-7

 Found - Orig. 8" D.Fir now 20", S.71°W., 42.9 ft. tree has been previously opened, scribing visible ("W" & other marks)

No trace of other BTs.

There is a large Fir in the NE. quad. with a BLM tag. Tree doesn't fit bearing. We cut open but find nothing.

Set Brass cap at cor. mkd: County Surveyors Office

T20S	R5W	S 32	S 33
T21S		S 5	S 4

1965

New BTs- 5" D.Fir, N.12°W., 9.6 ft. mkd. T20S R5W S32 CS BT
 12" Hemlock N.63°E., 31.3 ft. mkd. T20S R5W S33 CSBT
 8" Hemlock S.50°E., 22.7 ft. mkd. T21S R5W S4 CSBT.

BLM Resurvey by Floyd A. Brooks and Timothy A. Kent, Cadastral Surveyors, under Group #648, Surveyed Aug. 1967/Sept. 1971 - (DCSO records Vol. 37 Page(s) 15262-63)

 The Sec. Cor., remonumented by Rogers in 1965, with an iron post, 1" dia., firmly set, projecting 6" above ground, with brass cap mkd. in 1965, from which the remains of the original bearing trees:

A Fir 48" dia., bears N.65°E., 121 lks. dist., with scribe marks T20 visible on opened blaze. (Rec. N.75°E.)

A decayed Fir stump 26" dia., bears S.58°E., 34 lks. dist., with decayed blaze, no marks visible. (Rec. S.55°E.)

A Fir 21" dia., bears S.71°W., 65 lks. dist., with scribe marks 21W visible on decayed face of opened blaze.

A sawed Fir stump 33" dia., bears N.50°W., 64 lks. dist., with healed blaze. (Cont. Next Page)

TOWNSHIP 21 RANGE 05 POINT IDENTIFIER # 300700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 4 & 5; 32 & 33, T20-5

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

and bearing trees mkd. by Rogers:

A Hemlock 11" dia., bears N.65°E., 49 lks. dist., with scribe marks T20S R5W S33 CS BT visible on open double blaze.

A Fir 7" dia., bears N.11°E., 10½ lks. dist., with fragmentary scribe marks visible on pitched over double blaze.

A Hemlock 10" dia., bears S.48¼°E., 40½ lks. dist., with scribe marks T21S R5W S4 CS BT visible on open double blaze.

and a new bearing tree:

A Fir 8" dia., bears S.73°W., 90 lks. dist., mkd. T21S R5W S5 BT.

Add the marks BLM 1967 to the brass cap.