

PRIMARY CORNER DESCRIPTION 1/4 cor. for Secs. 28 and 33

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

GLO survey by Harvey Gordon and Charles T. Gardner, Deputy Surveyors, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 2 Page(s) 809)

Set ¼ sec. post, from which
A Fir 25" dia., bears N.72°W., 63 lks. dist.
A Fir 18" dia., bears S.69°W., 74 lks. dist.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew
Sept. 1965 - C.S. File 54/14-15A

Looked for, not found.

Malcolm Clark, Green Empire Inc. - March/Aug. 1972 - M 46-31

Set 2" Pipe with 3" alum. cap, from which
6" Fir N.61°E., 45.6 ft.
6" Fir S.2°W., 41.1 ft.

BLM resurvey by Wayne L. Rogers, Cadastral Surveyor, Group #1059, surveyed April/Dec. 1981 - (DCSO records Vol. 45 Page(s) 17318)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:
T 21 S R 5 W
1/4 S 28
 S 33
 1981

from which
A Fir 8" dia., bears N.47½°E., 33 lks. dist. mkd. ¼ S28 BT.
A Fir 6" dia., bears S.25¼°W., 60 lks. dist. mkd. ¼ S33 BT.
From this point, a corner established by Clark in 1972, bears S.75°38'E., 0.165 chs. dist., monumented with an alum. post, 2" dia., firmly set, projecting 2" above ground, with alum. cap mkd. Green Empire Inc. T21S R5W S 1/4 S28 S33 1972, from which BTs mkd. by Clark:
A Fir 10" dia., bears N.57 3/4°E., 68 lks. dist., with healed double blaze.
A Fir 10" dia., bears S.1°E., 62 lks. dist., with healed double blaze.

Fd. OK by L. Roberts, Jan. 2001 - M136-42

continued next page

TOWNSHIP 21 RANGE 05 POINT IDENTIFIER # 340200

PRIMARY CORNER DESCRIPTION 1/4 cor. for Secs. 28 and 33

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

Robert B. Ward - For: Seneca Jones Timber Co. - Nov. 2001 -
M 139-23

Found - 3¼" BLM brass cap dated 1981.
3" alum. cap on 2" alum. pipe dated 1972, set in
M 46-31 bears S.75°51'E., 10.85.

New - 8" G.Fir bears S.66½°E., 81.3' blazed, scribed "¼
S33 BT"
12" Maple in 4 stem clump bears S.36½°E., 68.7'
blazed, scribed "¼ S33 BT"

Note - BTs established during this survey have a red
painted band & face plus yellow BT tag.