

TOWNSHIP 21 RANGE 05 POINT IDENTIFIER # 340300

PRIMARY CORNER DESCRIPTION 1/4 cor. for Secs. 21 and 28

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Harvey Gordon and Charles T. Gardner, Deputy Surveyors, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 2 Page(s) 810)

Set ¼ sec. post, from which
A Fir 10" dia., bears S.55°W., 50 lks. dist.
A Fir 15" dia., bears N.79°W., 55 lks. dist.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - Nov. 1964 - C.S. File 49/68-40 & C.S. File 52/14-133

Looked for, not found.

Malcolm Clark, Green Empire, Inc. - Mar/Aug. 1972 - M 46-31

Set 2" Pipe with 3" alum. cap, from which
12" Fir N.37°W., 18.4 ft.
24" Cedar S.55°E., 78.1 ft.

BLM dependent resurvey by Wayne Rogers & Bryan Seibold Cadastral Surveyors & Robert Browning, Surveying Technician, under Group #1814, surveyed Aug. 1996/April 1998 - (DCSO rec. Vol. 53 Page(s) 20422-3)

The 1/4 sec. cor. of secs. 21 and 28, determined at record bearing and dist. from the remains of an OBT
A decayed fir stump, 36" diam., bears N.79°W., 55 lks., with scribe marks T and chaining notch above scribing visible on opened blaze.

At the corner point

Set a stainless steel post, 28" long, 2½" diam., 27" in the ground, with brass cap mkd.

T21S R5W
¼ $\frac{S\ 21}{S\ 28}$
1996

from which new bearing trees

A fir, 11" diam., bears N.16½°E., 23½ lks., mkd. ¼ S21 BT.

A fir, 10" diam., bears S.43½°E., 21 lks., mkd. ¼ S28 BT.

Deposit a magnet in a white plastic case at the base of the stainless steel post.

From this point, a point erroneously reestablished as the 1/4 sec. cor. of secs. 21 & 28 by Clark, in 1972, bears N.22°02'05"E., 0.198 chs.; monumented with an iron post, 2½" diam., firmly set, projecting 5" above ground, with aluminum cap mkd. T21S R5W S21 N ¼ S28 1972, from which the remains of bearing trees mkd. by Clark

A sawed cedar stump, 48" diam., bears S.60°E., 118 lks., with no marks visible. continued next page

TOWNSHIP 21 RANGE 05 POINT IDENTIFIER # 340300

PRIMARY CORNER DESCRIPTION 1/4 cor. for Secs. 21 and 28

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A sawed fir stump, 22" diam., bears N.40¼°W., 28 lks., with healed blaze.

Harvey Christensen, For: Guistina Land & Timber and Thomas Mulder - Sept. 1999 - M 133-32

Found - 3.25" 1996 BLM BC, 0.2 ft. above ground.
13" D.Fir N.17.5° 15.5 ft. scribing visible - healed face.
12" D.Fir S.41.5°E., 13.7 ft. scribing visible - healed face.
30" D.Fir N.79.5 ft. stump-scribing fragmented.
17" D.Fir S.35°W., 54.1 ft. blazed & scribed "¼ S28 BT"
15" D.Fir N.64.5°W., 38.9 ft. blazed & scribed "¼ S21 BT"
3" 1972 AC, 0.2 above ground N.26°E., 13.2 ft. Poage proportioned ¼ corner.
Note - 10/8/1999, we do not have the 1996 BLM resurvey filed in our office yet.