

TOWNSHIP 21 RANGE 05 POINT IDENTIFIER # 400140

PRIMARY CORNER DESCRIPTION 1/4 cor. for Secs. 33 & 34

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Harvey Gordon and Charles T. Gardner, Deputy Surveyors, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 2 Page(s) 805)

Set ¼ sec. post, from which
A Fir 12" dia., bears S.37°E., 162 lks. dist.
A Fir 18" dia., bears S.60°W., 98 lks. dist.

Ben B. Irving, Deputy Co. Surveyor - Wit: J.S. Snyder; Harvey Eppstein; Elwood Nelson - June 17, 1938 - C.S. File 37/195

Location identified by distance from sec. cor. dist. from small creek.
O.B.T., S.60°W., 98 lks., blazed and previously chopped out. All scribe marks obliterated.
Stump O.B.T., rotted and no scribe marks S.37°E., 162 lks.
Set for corner, sandstone 8" x 10" x 18", 10" in ground, chiseled X on top ¼ S CS.
Marked new trees:
Fir 12" dia., N.62°W., 49.7 ft.
Oak 12" dia., S.10°E., 2.5 ft.
Blazed and scribed "¼S CS BT".

Oscar Thiel - For: Ernest E. Woolley - June 21, 1945 - Thiel Book 1 page 11

Old trees all gone. In a former survey marked a Cedar 10" S.41°W., 47. Set a dogwood stake.

Wilford N. Haines, #239 - For: Keith Roberts - April 1959 - C.S. File 51/14

Found stump of 12" Fir, N.62°W., 49.7 ft.
Rock and 12" Oak has been destroyed by road construction.
Set Lot marker, 1" x 1" x 36" T. Iron with cap inscribed "Wilford N. Haines #239 Survey Point", N.62°W., 10.0 ft. from ¼ corner.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - Stoffel and Stone, crew - Nov. 27, 1964 - C.S. file 49/68-45

Found - T Iron and cap set by Haines, N.62°W., 10.0 ft.
Stump of BT, 12" Fir N.62°W., 49.7 ft., scribing visible.
Old rotted Fir stump, S.37°E., 107 ft., orig. BT.
No marks visible.

(Cont. Next Page)

TOWNSHIP 21 RANGE 05 POINT IDENTIFIER # 400140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 33 and 34

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

New BTs- 9" W.Oak N.30°W., 11.5 ft. mkd. ¼ S33 CS BT.
20" D.Fir N.12°E., 41.2 ft. mkd. ¼ S34 CS BT.
(New BTs bearing and distance from Wit. Cor. - Haines T Iron
set for ¼ corner, other found stump dist. & brg. from ¼ cor.)

BLM resurvey by Wayne L. Rogers, Cadastral Surveyor, Group
#1059, surveyed April/Dec. 1981 - (DCSO records Vol. 45
Page(s) 17328)

The ¼ sec. cor., perpetuated and recorded by Irving in 1938,
determined at record bearing and distance from the remains of
an original bearing tree

A decayed Fir stump, size indeterminate bears s.37°E., 162
lks. dist., no marks visible.

and the remains of a bearing tree mkd. by Irving:

A Fir stump 24" dia., bears N.62°W., 75 lks. dist., with
scribe marks BT visible on opened blaze.

At the corner point

Set a brass tablet, 3¾" long, 3 1/2" dia., stem, in drill
hole, in exposed bedrock, with top mkd.

T 21 S R 5 W
1/4
S 33 | S 34
1981

from which new bearing trees:

An Oak 22" dia., bears S.60°E., 97 lks. mkd. ¼ S34 BT.

A Fir 8" dia., bears N.25½°W., 60 lks. mkd. ¼ S33 BT.

From this point, a corner established and recorded by Haines
in 1959, bears N.58°W., 0.15 chs. dist., monumented with a T
shaped iron rod, 1" dia., firmly set, projecting 16" above
ground, with brass cap mkd. by Haines, from which the remains
of bearing trees mkd. by Milo Godfrey in 1964,

A Fir snag 24" dia., bears N.12°E., 62 lks. dist., with
scribe marks ¼ S34 CS BT visible on open blaze.

An Oak 14" dia., bears N.28½°W., 17 lks. dist. with healed
double blaze.

Survey by Daniel Baker - For: Weyerhaeuser Co. - Feb. 1996 -
M 124-12

Found - US BLM brass cap dated 1981.

Broken Haines T Iron, N.70°W., 10.3 ft. (Rec.
N.62°W., 10.0 ft. 1959 Haines)

27" Oak S.60°E., 63.3 ft. to set spike, closed face
(Rec. S.60°E., 97 lks. 1981 BLM)

(Cont. Next Page)

TOWNSHIP 21 RANGE 05 POINT IDENTIFIER # 400140

PRIMARY CORNER DESCRIPTION 1/4 cor. for Secs. 33 and 34

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

18" Fir stump N.24°W., 39.0 ft. closed face (Rec.
N.25½°W., 60 lks. 1981 BLM)
New BTs- 7" Fir S.51°W., 47.0 ft. to "W" nail scribed ¼ S33
BT.
22" Oak S.88°E., 136.5 ft. to "W" nail "¼ S34 BT."
10" Fir N.48°E., 237.3 ft. to "W" nail "¼ S34 BT."

Found OK by R. Ward, Oct. 2001 - M139-25