

TOWNSHIP 21 RANGE 05 POINT IDENTIFIER # 400400

PRIMARY CORNER DESCRIPTION Cor. Secs. 15, 16, 21 & 22

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Harvey Gordon and Charles T. Gardner, Deputy Surveyors, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 2 Page(s) 807)

-----  
Set post cor. of secs. 15, 16, 21 & 22, from which  
A Cedar, 10" dia., bears N.83°W., 95 lks.  
A Cedar, 12" dia., bears S.51°W., 55 lks.  
A Cedar, 36" dia., bears S.17°E., 39 lks.  
A Fir, 18" dia., bears N.65°E., 78 lks.

BLM dependent resurvey by Wayne Rogers & Bryan Seibold Cadastral Surveyors & Robert Browning, Surveying Technician, under Group #1814, surveyed Aug. 1996/April 1998 - (DCSO rec. Vol. 53 Page(s) 20409-10)

-----  
Point for the cor. of secs. 15, 16, 21 and 22, at proportionate dist.; there is no remaining evidence of the original cor.

Set a stainless steel post, 28" long, 2½" diam., 25" in the ground, with brass cap mkd.

T21S R5W  
S 16 | S 15  
S 21 | S 22  
1996

from which

- A fir, 19" diam., bears N.72½°E., 50 lks., mkd. T21S R5W S15 BT.
- A fir, 17" diam., bears S.53½°E., 30 lks., mkd. T21S R5W S22 BT.
- A fir, 10" diam., bears S.64½°W., 62 lks., mkd. T21S R5W S21 BT.
- A fir, 35" diam., bears N.11°W., 65 lks., mkd. T21S R5W S16 BT.

Deposit a magnet in a white plastic case at the base of the stainless steel post.