

PRIMARY CORNER DESCRIPTION Sec. Cor. for 9, 10, 15 and 16

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

<p>GLO survey by Harvey Gordon and Charles T. Gardner, Deputy Surveyors, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 2 Page(s) 808)</p> <p>-----</p> <p>Set post cor. of secs. 9, 10, 15 and 16, from which</p> <ul style="list-style-type: none"><li>A Fir 8" dia., bears N.42°E., 52 lks. dist.</li><li>A Fir 10" dia., bears N.70°W., 66 lks. dist.</li><li>A Fir 18" dia., bears S.61°W., 39 lks. dist.</li><li>A Fir 5" dia., bears S.75°E., 47 lks. dist.</li></ul>
<p>Fd. and Used in GLO survey by W. P. Wright, U.S. Deputy Surveyor, under Contract #514, dated August 27, 1884 (DCSO records Vol. 2 Page(s) 818)</p>
<p>Wilford N. Haines, #239 - For: Harold Woolley - Dec.1957 - M 7-64</p> <p>-----</p> <p>Set Lot marker, 1" x 1" x 36" T Iron with brass cap inscribed Survey Point Wilford Haines #239.</p> <p>Scribed- 6" Fir N.76°E., 23.4 ft.</p> <ul style="list-style-type: none"><li>30" Fir S.75°E., 31.0 ft. (may be orig. 5" BT, S.75°E., 47 lks.)</li></ul>
<p>Douglas County Surveyors Office - Vernon "Ray" Tracy and crew July 1965 - C.S. File 54/14-21</p> <p>-----</p> <p>Found - Haines T Iron.</p> <ul style="list-style-type: none"><li>6" now 7" Fir N.76°E., 23.4 ft., shows good scar.</li><li>30" now 31" Fir S.75°E., 31.0 ft., shows T21S R5W S15 BT, bark scribe.</li></ul> <p>New BTs- 5" D.Fir N.62°W., 13.9 ft. mkd. S9 CS BT.</p> <ul style="list-style-type: none"><li>9" D.Fir S.37°W., 17.5 ft. mkd. T21S R5W S16 CS BT</li></ul>
<p>BLM dependent resurvey by Wayne Rogers &amp; Bryan Seibold Cadastral Surveyors &amp; Robert Browning, Surveying Technician, under Group #1814, surveyed Aug. 1996/April 1998 - (DCSO rec. Vol. 53 Page(s) 20411-2)</p> <p>-----</p> <p>The cor. of secs. 9, 10, 15 &amp; 16, perpetuated by Haines, in 1957, further perpetuated by Tracy, in 1965, monumented with a "T" iron, 1x1", firmly set, projecting 8" above ground, with brass washer, 1" diam., mkd. WILFORD N. HAINES 239 SURVEY POINT DRAIN ORE., from which the remains of the OBTs</p> <ul style="list-style-type: none"><li>A fir, 41" diam., bears S.75°E., 47 lks., rescribed by Haines, with scribe marks T21S visible on the bark.</li><li>A root hole, bears S.61°W., 39 lks., with a fir trunk, size indeterminate, alongside, no marks visible.</li></ul> <p>continued next page</p>

TOWNSHIP 21 RANGE 05 POINT IDENTIFIER # 400500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 9, 10, 15 and 16

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

and a bearing tree mkd. by Haines

A fir, 16" dia. bears N.76°E., 35½ lks. with healed blaze.  
and bearing trees mkd. by Tracy

A fir, 21" dia. bears S.37°W., 26½ lks. with healed double  
blazes.

A fir, 19" dia. bears N.62°W., 21 lks., with healed double  
blazes.

At the corner point

Set a stainless steel post, 28" long, 2½" dia., 24" in the  
ground, directly over the "T" iron, with brass cap mkd.

T21S R5W  
S 9 | S 10  
S 16 | S 15  
1996

Deposit a magnet in a white plastic case at the base of the  
stainless steel post.