

PRIMARY CORNER DESCRIPTION 1/4 cor. for Secs. 9 and 10

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W. P. Wright, U.S. Deputy Surveyor, under Contract #514, dated August 27, 1884 (DCSO records Vol. 2 Page(s) 818-19)

Set post 4" dia., 4 ft. long, with mkd. stone 12" in ground for ¼ sec. cor. mkd. ¼ S on W. face, from which
A Cedar 12" dia., bears N.25°E., 22 lks. dist. mkd. ¼ S BT.
A Cedar 12" dia., bears N.81°W., 50 lks. dist. mkd. ¼ S BT.

Wilford N. Haines, #239 - For: Harold Woolley - Dec. 1957 - M 7-64

Set Lot Marker, 1" x 1" x 36" T Iron with brass cap inscribed Wilford Haines #239.
Scribed- 20" Cedar N.61°E., 41.5 ft.
30" Cedar stub N.61°E., 12.0 ft.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew Aug/Sept. 1965 - C.S. File 54/14-15

Found - Haines T Iron at cor. and BTs as recorded by Haines.
20" Cedar N.61°E., 41.5 ft., now a shattered stump 6.0 ft. high, shows "¼ S10 BT" and Haines' button.
30" Cedar stub N.61°E., 12.0 ft., shows "¼S BT" and Haines button.
No trace of original BTs.
New BTs- 30" D.Fir N.14°E., 39.8 ft. mkd. ¼ S10 CS BT.
10" D.Fir S.34°W., 37.7 ft. mkd. ¼ S9 CS BT.
Corner lies 20 ft. North of small creek flowing S.E.

Douglas Co. Surveyors Office - Gregory Quibell, Deputy - Debbie Stewart, witness - Sept. 15, 1981 - C.S. File 61/27-41

Found - Haines T Iron with brass button, firmy set, protruding 9" out of the ground.
6 ft. high snag (orig. 20" Cedar) with visible ¼ S10 BT and Haines button, bears N.61°E., 41.5 ft.
30" Cedar stump lying on its side, badly decayed, with scribed ¼ S BT. Stump hole bears N.61°E., 12 ft.
Stump (orig. 30" Fir) (per 1965), with visible ¼ S10 CS BT, bears N.14°E., 39.8 ft.
15" Hemlock (Orig. 10" Fir) (per 1965), bears S.34°W., 37.7 ft. with well healed double blaze.

(Cont. Next Page)

TOWNSHIP 21 RANGE 05 POINT IDENTIFIER # 400540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 9 and 10

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

No trace of original BTs.
Set Brass cap at cor. mkd: County Surveyors Office
T 21 S R 5 W
¼ S 9 | S10
1981
I replace the referenced out T Iron in ground at South edge
of cap.
New BTs- 9" Fir scribed ¼ S9 CS BT in double blaze bears
N.68°W., 24.0 ft.
9" Fir scribed ¼ S10 CS BT in double blaze bears
N.13°E., 14 ft.
12" Fir scribed ¼ S10 CS BT in double blaze bears
N.73°E., 31.5 ft.