

PRIMARY CORNER DESCRIPTION Sec. Cor. for 3, 4, 9 and 10

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by W. P. Wright, U.S. Deputy Surveyor, under Contract #514, dated August 27, 1884 (DCSO records Vol. 2 Page(s) 819)

Set post 6" dia., 4 ft. long with mkd. stone, 12" in ground, for cor. to secs. 3, 4, 9 and 10, mkd. T21S S3 on NE.; R5W S10 on SE.; S9 on SW.; S4 on NW. faces, with 3 notches on E. and 5 on S. edges, from which
A Fir 12" dia., bears N.53°E., 19 lks. dist. mkd. T21S R5W S3 BT.
A Fir 12" dia., bears S.83°E., 12 lks. dist. mkd. T21S R5W S10 BT.
A Fir 12" dia., bears S.49°W., 61 lks. dist. mkd. T21S R5W S9 BT.
A Fir 18" dia., bears N.65°W., 25 lks. dist. mkd. T21S R5W S4 BT.

Wilford N. Haines, #239 - For: Harold Woolley - Dec. 1957 - M 7-64

Set Lot Marker 1" x 1" x 36" T Iron with brass cap inscribed Wilford Haines #239.
Found - 30" Fir N.65°W., 25 lks.
12" Fir S.49°W., 61 lks.
Scribed- 36" Fir N.01°E., 15.0 ft.
30" Fir S.05°W., 7.5 ft.

Bruce A. Shaner - For: BLM - Feb. 12, 1973 - M 47-72

Found - 3/4" T Iron.
26" D.Fir stump, bears N.65°W., 16.5 ft, to face.
34" D.Fir, face visible, bears S.5°W., 7.5 ft.
32" D.Fir stump, scribe vis., bears N.1°E., 15.0 ft.
Set Brass cap mkd. T21S R5W WM S4 S3 S9 S10 1973.

BLM Resurvey by Bryan S. Seibold, Cadastral Surveyor, under Group #1564, Surveyed Aug/Nov. 1990 - (DCSO records Vol. 50 Page(s) 19053)

The Sec. Cor., perpetuated by Haines in 1957, further perpetuated by Shaner in 1973, monumented with an iron post 1½" dia., firmly set, projecting 9" above ground with brass cap mkd. in 1973, from which the remains of the original bearing trees:
A sawed rotted stump 17" dia., bears S.49°W., 61 lks. dist., no marks visible.
(Cont. Next Page)

TOWNSHIP 21 RANGE 05 POINT IDENTIFIER # 400600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 3, 4, 9 and 10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A sawed Fir stump 22" dia., bears N.65°W., 25 lks. dist., with fragmentary scribe marks visible on open blaze. and the remains of the bearing trees mkd. by Haines:
A sawed Fir stump 31" dia., bears N.2°E., 23½ lks. dist., with fragmentary scribe marks visible on a bark blaze.
A Fir 37" dia., bears S.3½°W., 11½ lks. dist., with healed double blaze.
and new bearing trees:
A Fir 6" dia., bears N.41°E., 34½ lks. dist., mkd. T21S R5W S3 BT.
A Fir 6" dia., bears S.46°E., 51½ lks. dist. mkd. T21S R5W S10 BT.
A Fir 7" dia., bears N.32°W., 15 lks. dist. mkd. T21S R5W S4 BT.
Found a T shaped iron rod, 1" dia., firmly set, projecting 6" above ground, with brass washer mkd. Wilford N. Haines 239 Survey Point Drain Ore., alongside iron post.