

TOWNSHIP 21 RANGE 05 POINT IDENTIFIER # 440240

PRIMARY CORNER DESCRIPTION Center 1/4 cor. for Sec. 27

Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____

Survey by Wilford N. Haines - For: Churchill and Woolley Logging - Dec. 1967 - M 35-12

Set 5/8" steel rod, from which scribed:
24" D.Fir S.83°W., 77.0 ft.
36" D.Fir N.36°E., 22.5 ft. (This tree looks like old BT)

BLM Resurvey by Bryan S. Seibold, Cadastral Surveyor, under Group #1639, surveyed Sept. 1992/April 1993. - (DCSO records Vol. 51 Page(s) 19408)

The Center 1/4 Cor., established by Haines in 1967, and is accepted as the corner; monumented with an iron rod, 5/8" dia., firmly set, projecting 4" above ground, from which bearing trees mkd. by Haines:

A Fir 40" dia., bears N.35¼°E., 33½ lks. dist., with healed blaze.

A Fir 25" dia., bears S.82°W., 116 lks. dist., with healed blaze.

At the corner point

Set a stainless steel post 28" long, 2½" dia., 20" in the ground, directly over the iron rod, with brass cap mkd.

T21S R5W
C 1/4 S 27
1993

No new accessories taken.

Deposit white "DEEP-1" magnetic marker at base of stainless steel post.