

TOWNSHIP 21 RANGE 05 POINT IDENTIFIER # 440500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 10 and 15

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Harvey Gordon and Charles T. Gardner, Deputy Surveyors, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 2 Page(s) 808)

-----  
Set ¼ sec. post, from which  
A Fir 36" dia., bears S.54°E., 44 lks. dist.  
A Fir 20" dia., bears N.50°E., 50 lks. dist.

Wilford N. Haines, #239 - For: Harold Woolley - Dec.1957 - M 7-64

-----  
Set Lot Marker 1" x 1" x 36" T Iron with brass cap inscribed Survey Point Wilford Haines #239.  
Scribed- 18" Fir S.41°E., 65.5 ft.  
12" Fir N.76°W., 19.7 ft.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew Aug/Sept. 1965 - C.S. File 54/14-11

-----  
Found - Haines T Iron.  
18" now 20" D.Fir S.41°E., 65.5 ft., scar healed, alive and OK.  
12" now 14" D.Fir N.76°W., 19.7 ft., broken top and bark scribed.  
New BT - 9" Hemlock N.42°E., 49.6 ft. mkd. ¼ S10 CS BT.