

PRIMARY CORNER DESCRIPTION 1/4 cor. for Secs. 3 and 10

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by W. P. Wright, U.S. Deputy Surveyor, under Contract #514, dated August 27, 1884 (DCSO records Vol. 2 Page(s) 819-20)

Set post 4" dia., 4 ft. long, with mkd. stone, 12" in ground for ¼ sec. cor., mkd. ¼ S on N. face, from which
An Oak 7" dia., bears N.23°E., 26 lks. dist. mkd. ¼ S BT
A Maple 6" dia., bears S.70°W., 43 lks. dist. mkd. ¼ S BT

Wilford N. Haines, #239 - For: Harold Woolley - Dec. 1957 - M 7-64

Set Lot Marker 1" x 1" x 36" T Iron with brass cap inscribed Wilford Haines #239.
Scribed- 18" Fir N.27°E., 39.0 ft.
20" Fir S.47°W., 42.6 ft.

Bruce A. Shaner - For: BLM - Feb. 12, 1973 - M 47-72

Found - 3/4" T Iron.
26" D.Fir bears N.27°E., 39.0 ft.
26" D.Fir bears S.47°W., 42.6 ft.
Set Brass cap alongside T Iron, mkd. T21S R5W WM ¼ S3 S10 1973.

BLM Resurvey by Bryan S. Seibold, Cadastral Surveyor, under Group #1564, Surveyed Aug/Nov. 1990 - (DCSO records Vol. 50 Page(s) 19052)

The ¼ sec. cor., reestablished by proportionate measurement by Haines in 1957, perpetuated by Shaner in 1973,; there is no remaining evidence of the original corner, therefore, this position is accepted as the corner, monumented with an iron post 1½" dia., firmly set, projecting 7" above ground, with brass cap mkd. in 1973
from which the remains of the bearing trees mkd. by Haines:
A root hole bears N.27 ¾°E., 54 lks. dist., with uprooted Fir alongside 26" dia., with scribe marks ¼ S3 BT visible on a bark blaze.
A sawed Fir stump 31" dia., bears S.50½°W., 64½ lks. dist., with healed double blaze.
and a new bearing tree:
A Fir 11" dia., bears N.9°E., 49 lks. dist. mkd. ¼ S3 BT
No suitable tree available in sec. 10.
Found a T shaped Iron rod, 1" dia., firmly set, projecting 2" above ground, with brass washer mkd. Wilford N. Haines 239 Survey Point Drain Ore., alongside iron post.