

TOWNSHIP 21 RANGE 05 POINT IDENTIFIER # 500240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 26 and 27

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Harvey Gordon and Charles T. Gardner, Deputy Surveyors, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 2 Page(s) 801)

-----  
Set ¼ sec. post, from which  
A Fir 8" dia., bears N.71°W., 138 lks. dist.  
A Fir 6" dia., bears N.70°E., 183 lks. dist.

-----  
O.F. Thiel - For: J.A. Johnson - Jan. 1901 - F.B. 113 Pg. 104  
-----  
Fir Post. Maple 10" S.7°E., 31 lks.

-----  
Arthur R. Evans - Nov. 1951 - C.S. File 40/389 and M 14-50  
-----  
Found axle and old scribed stake. Also old BT, N.71°W., 91.0 ft. 36" Fir.  
New BT - N.10°E., 13.8 ft., blazed and scribed.

-----  
Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - Stoffel and Stone, crew - Dec. 1964 - C.S. File 49/68-53  
-----  
Found - Steel axle.  
36" Fir stump, N.71°W., 91 ft., bark scribed, cut open and found scribing "1" at 8" dia.  
36" Fir stump, N.70°E., 120.8 ft., top of stump shows burl wood near orig. dia.  
Tree mkd. by Evans, 22" D.Fir N.10°E., 13.8 ft., scribing visible.  
New BT - 14" D. Fir N.45°W., 18.7 ft. mkd. ¼ S27 CS BT.  
Corner is in E. & W. fence line along N. edge of open field.

-----  
BLM Resurvey by Bryan S. Seibold, Cadastral Surveyor, under Group #1639, surveyed Sept. 1992/April 1993. - (DCSO records Vol. 51 Page(s) 19398)

-----  
The ¼ sec. cor., perpetuated by Evans in 1951, recovered by Gilbert Gardner in 1954-55 recorded on map file M 16-6, further perpetuated by Godfrey in 1964, further recovered by Haines in 1967, recorded on map file M 35-12; monumented with an axle 1½" dia. firmly set, projecting 12" above ground, from which the remains of the original bearing trees:  
A sawed Fir stump 36" dia., bears N.75°E., 187 lks. dist., no marks visible. (Rec. N.70°E., 183 lks.)  
A sawed Fir stump 38" dia., bears N.74°W., 140 lks. dist., with fragmentary scribe marks visible on the bark. (Rec. N.71°W., 138 lks.)

(Cont. Next Page)

TOWNSHIP 21 RANGE 05 POINT IDENTIFIER # 500240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 26 and 27

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

and a bearing tree mkd. by Evans:  
A Fir 33" dia., bears N.14¼°E., 21 lks. dist., with healed double blaze.

and a bearing tree mkd. by Godfrey:  
A Fir 23" dia., bears N.45½°W., 28½ lks. dist. with healed double blaze.

At the corner point  
Set an stainless steel post, 28" long, 2 1/2" dia., 24" in the ground, directly over the axle, with brass cap mkd:

T 21 S R 5 W  
1/4  
S 27 | S 26  
1993

No new accessories taken.  
Deposit white "DEEP-1" magnetic marker at base of stainless steel post.  
Corner is located in a woven wire fence extending E. and W.

Survey by Les Roberts - For: Giustina Resources Inc. - Jan. 1996 - M 123-29

-----  
Found - 1993 BLM Iron pipe and brass cap.  
24" Fir N.10°E., 13.8 ft., scar visible. 1951 BT  
18" Fir N.45°W., 18.7 ft., scar visible. 1964 BT