

TOWNSHIP 21 RANGE 05 POINT IDENTIFIER # 500400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 14, 15, 22 and 23

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Harvey Gordon and Charles T. Gardner, Deputy Surveyors, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 2 Page(s) 802)

Set post cor. of secs. 14, 15, 22 and 23, from which
A Fir 36" dia., bears S.60°E., 23 lks. dist.
A Fir 24" dia., bears S.50°W., 61 lks. dist.
A Dogwood 8" dia., bears N.57°W., 49 lks. dist.
A Dogwood 10" dia., bears N.60°E., 60 lks. dist.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew
Sept. 1965 - C.S. File 54/14-11A

Looked for, not found.

Survey by Les Roberts - For: Giustina Timber Co. and Giustina Resources Inc. - July 30, 1993 - M 117-53

Set corner from stump pattern and creek calls.
Found - Root hole, S.60°E., 14.2 ft., 1856 BT.
 Root hole, S.50°W., 40.3 ft., 1856 BT.
Set 5/8" x 30" Iron pin with yellow plastic cap.
New BTs- 8" Fir S.43°W., 16.0 ft., scribed/painted red.
 10" Fir N.52°W., 9.2 ft., scribed/painted red.
 12" Fir N.27°E., 20.0 ft., scribed/painted red.
 18" Fir S.23°E., 14.1 ft., scribed/painted red.