

TOWNSHIP 21 RANGE 05 POINT IDENTIFIER # 500440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 14 and 15

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Harvey Gordon and Charles T. Gardner, Deputy Surveyors, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 2 Page(s) 803)

-----  
Set ¼ sec. post, from which  
A Fir 18" dia., bears N.78°W., 28 lks. dist.  
A Laurel 10" dia., bears S.70°E., 17 lks. dist.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew  
Sept. 1965 - C.S. File 54/14-11A

-----  
Looked for, not found.

Survey by Les Roberts - For: Giustina Timber Co. & Giustina Resources, Inc. - July 30, 1993 - M 117-53

-----  
No evidence found of original corner.  
Set 5/8" x 30" Iron pin by proportionate measure, from which  
18" Fir S.82°E., 2.4 ft., scribed/painted red.  
20" Fir S.18°W., 18.2 ft., scribed/painted red.  
12" Fir S.81°W., 43.9 ft., scribed/painted red.  
24" Fir S.55°E., 21.5 ft., scribed/painted red.