

TOWNSHIP 21 RANGE 05 POINT IDENTIFIER # 500500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 10, 11, 14 and 15

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

GLO survey by Harvey Gordon and Charles T. Gardner, Deputy Surveyors, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 2 Page(s) 803)

Set post cor. of secs. 10, 11, 14 and 15, from which
A Fir 10" dia., bears N.64°E., 30 lks. dist.
A Fir 12" dia., bears N.30°W., 65 lks. dist.
A Fir 7" dia., bears S.16°W., 33 lks. dist.
A Laurel 8" dia., bears S.25°E., 21 lks. dist.

Wilford N. Haines, #239 - For: Harold Woolley - Dec. 1957 - M 7-64

This corner set from local topography as shown on map.
Found blazes on stump and a snag South of position corner.
Scribed- 6" Fir S.33°E., 18.2 ft.
8" Fir N.21°40'E., 21.6 ft.
8" Fir N.85°50'W., 38.0 ft.
6" Fir S.83°30'W., 42.4 ft.
Set Lot Marker.

Survey by Les Roberts - For: Seneca Sawmill Co. and Giustina Resources, Inc. - Aug. 15, 1994 - M 120-64

Found - 1957 Haines T Iron.
18" Fir N.86°W., 38 ft., scar visible. 1957 BT.
20" Fir N.21°E., 21.6 ft., scar visible. 1957 BT.
12" Fir S.70°W., 36.1 ft., scribe vis. No record.
14" Fir S.51°E., 35.3 ft., scribe vis. No record.