

TOWNSHIP 21 RANGE 05 POINT IDENTIFIER # 500600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 2, 3, 10 and 11

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Harvey Gordon and Charles T. Gardner, Deputy Surveyors, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 2 Page(s) 804)

Set post cor. of secs. 2, 3, 10 and 11, from which
A Fir 60" dia., bears S.45°E., 21 lks. dist.
A Fir 50" dia., bears N.50°E., 45 lks. dist.
A Fir 70" dia., bears S.83°W., 13 lks. dist.
A Fir 8" dia., bears N.85°W., 11 lks. dist.

Fd. and used in GLO survey by W. P. Wright, U.S. Deputy Surveyor, under Contract #514, dated August 27, 1884 (DCSO records Vol. 2 Page(s) 817)

Wilford N. Haines, - For: Harold Woolley - Dec. 1957 - M 7-64

Set Lot Marker, 1" x 1" x 36" T Iron with brass cap inscribed "Survey Point Wilford Haines #239"
Found - 8" stub, N.52°W., 7.26 ft., scribed.
60" stump, S.51°E., 13.86 ft.
70" stump, S.72°W., 8.58 ft.
50" stump, N.41°30'E., 29.7 ft.
Scribed- 8" Madrone S.36°W., 25.5 ft.
10" Fir N.81°40'W., 8.9 ft.
6" Chinquapin S.73°E., 25.3 ft.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew Aug/Sept. 1965 - C.S. File 54/14-14

Found - Haines T Iron and BTs as recorded as follows:
8" now 10" Madrone S.36°W., 25.5 ft., bark scribe almost completely disappeared.
10" now 14" D.Fir N.81°40'W., 8.9 ft., shows good scar.
6" now 9" Chinquapin S.73°E., 25.3 ft., bark scribe in very poor condition.
New BTs- 10" Madrone S.36°W., 25.5 ft. mkd. T21S R5W S10 CS BT. (Rescribed)
9" Chinq. S.73°E., 25.3 ft. mkd. T21S R5W S11 CS BT. (Rescribed)
8" Chinq. N.53°E., 24.4 ft. mkd. T21S R5W S2 CS BT.

Bruce A. Shaner - For: U.S. Bureau of Land Management - Feb. 12, 1973 - M 47-72

Found - 3/4" T Iron.
10" Chinquapin bears S.73°E., 25.3 ft.
(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. Cor. for 2, 3, 10 and 11

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Found - 8" chinquapin bears N.53°E., 24.4 ft.
10" Madrone bears S.36°W., 25.5 ft.
16" D.Fir bears N.81 3/4°W., 8.9 ft.
Set Brass cap alongside T Iron, mkd. "T21S R5W WM S3 S2 S10 S1 1973".

BLM Resurvey by Bryan S. Seibold, Cadastral Surveyor, under Group #1564, Surveyed Aug/Nov. 1990 - (DCSO records Vol. 50 Page(s) 19049-50)

The Sec. Cor., perpetuated by Haines in 1957, further perpetuated by Tracy in 1965, and futher perpetuated by Shaner in 1973, monumented with an iron post, 1½" dia., firmly set, projecting 9" above ground with cap mkd. in 1973, from which the remains of the original bearing trees:

A rotted stump 40" dia., bears N.40½°E., 47½ lks. dist., no marks visible. (Rec. N.50°E., 45 lks.)

A rotted stump 40" dia., bears S.51½°E., 22½ lks. dist., no marks visible. (Rec. S.45°E., 21 lks.)

A rotted stump 50" dia., bears S.71°W., 18 lks. dist., no marks visible. (Rec. S.83°W., 13 lks.)

A rotted stump 15" dia., bears N.55½°W., 12 lks. dist., no marks visible. (Rec. N.85°W., 11 lks.)

and bearing trees mkd. by Haines:

A Chinquapin 13" dia., bears S.74°E., 38 lks. dist., with fragmentary scribe marks visible on partially healed blaze.

A Madrone 13" dia., bears S.36°W., 38½ lks. dist., with healed blaze.

A Fir 25" dia., bears N.81½°W., 14 lks. dist., with healed blaze.

and a bearing tree mkd. by Tracy:

A Chinquapin 10" dia., bears N.53½°E., 36½ lks. dist., with healed blaze.

Found a "T" shaped iron rod 1" dia., firmly set, projecting 12" above ground, with brass washer mkd. WILFORD N. HAINES 239 SURVEY POINT DRAIN, ORE. alongside iron post.

Corner is located on the N. edge of a ridge, extending N.45°E. and S.45°W.

Fd. OK, May 1994 - M 120-64