

TOWNSHIP 21 RANGE 05 POINT IDENTIFIER # 540200

PRIMARY CORNER DESCRIPTION 1/4 cor. for Secs. 26 and 35

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

GL0 survey by Harvey Gordon and Charles T. Gardner, Deputy Surveyors, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 2 Page(s) 800)

Set ¼ sec. post, from which
A Fir 36" dia., bears S.46°W., 68 lks. dist.
A Fir 10" dia., bears North, 51 lks. dist.

Douglas Co. Surveyors Office - Dec. 1964 - C.S. File 49/68-52

Looked for, not found.

Survey by Les Roberts - For: Giustina Resources Inc. - Jan. 1996 - M 123-29

No original evidence found.
Set 5/8" x 30" Iron pin w/yellow plastic cap mkd. "Roberts PLS 1039", by single proportionate measurement, from which new BTs:
8" Maple N.36°E., 49.1 ft., scribed/painted red.
8" Fir S.45°E., 11.9 ft., scribed/painted red.
8" Fir S.64°W., 22.7 ft., scribed/painted red.
10" Fir N.08°W., 35.0 ft., scribed/painted red.

BLM dependent resurvey by Wayne Rogers & Bryan Seibold Cadastral Surveyors & Robert Browning, Surveying Technician, under Group #1814, surveyed Aug. 1996/April 1998 - (DCSO rec. Vol. 53 Page(s) 20396)

The ¼ sec. cor. of secs. 26 & 35, reestablished by proportionate measurement by Roberts, in 1996, There is no remaining evidence of the original corner, therefore, this position is accepted as the cor.; monumented with an iron rod, 5/8" diam., firmly set, projecting 1" above ground, with yellow plastic cap mkd. ROBERTS PLS 1039, from which the remains of bearing trees mkd. by Roberts
A root hole, bears S.45°E., 18 lks., with uprooted fir, 9" dia., alongside, with scribe marks ¼ S35 BT visible on open blaze.
A root hole, bears S.64°W., 34½ lks., with uprooted fir, 9" diam., alongside, with scribe marks ¼ S35 BT visible on open double blazes.
A root hole, bears N.8°W., 53 lks., with uprooted fir, 10" dia., alongside, with scribe marks ¼ S26 BT visible on open double blazes.

At the corner point
continued next page

TOWNSHIP 21 RANGE 05 POINT IDENTIFIER # 540200

PRIMARY CORNER DESCRIPTION 1/4 cor. for Secs. 26 and 35

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

Drive an aluminum cap, 2". diam., onto the iron rod, with top
mkd.

T 21 S R 5 W

¼ $\frac{S\ 26}{S\ 35}$

1997

from which new bearing trees

A maple, 8" dia., bears N.44¼°E., 202 lks., mkd. ¼ S26 BT.

The most westerly trunk of a double trunk maple, 11" dia.,
bears S.54¼°E., 173 lks., mkd. ¼ S35 BT.

Survey by Les Roberts - for: W.E. McArthur & Assoc. - Dec.
1997 - M 128-1

Found - 1997 BLM iron rod with aluminum cap
8" Maple stump, N.36°E., 49.1' (scribe vis.) 1996 BT
8" Maple, N.44°E. 133.4' (scribe vis.), 1997 BT
10" Maple, S.54°E., 114.0' (scribe vis.), 1997 BT.
SE, SW, & NW bearing trees set in survey M 123-29
were destroyed by recent logging.