

PRIMARY CORNER DESCRIPTION Sec. Cor. for 13, 14, 23 and 24

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Harvey Gordon and Charles T. Gardner, Deputy Surveyors, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 2 Page(s) 796)

-
- Set post cor. of secs. 13, 14, 23 and 24, from which
- A Fir 40" dia., bears N.9½°E., 78 lks. dist.
 - A Fir 6" dia., bears S.72°E., 108 lks. dist.
 - A Fir 20" dia., bears S.28°W., 72 lks. dist.
 - A Fir 24" dia., bears N.74°W., 86 lks. dist.

Survey by Jim S. Peterson - For: Doug Smith - June 1977 (filed Oct. 26, 1977) - M 65-47

-
- Found - Rotted Fir stump, bears N.87°15'W., 56.76 ft. 9Rec. N.74°W., 56.76 ft.)
- 80" D.Fir bears S.65°58'E., 71.28 ft. (Rec. S.72°E., 71.28 ft.)
- Set 3/4" Iron Pipe.
- New BTs-
- 8" D.Fir bears N.60°E., 36.8 ft. to center, scribed S13 BT.
 - 14" D.Fir bears S.54°E., 20.6 ft. to center scribed S24 BT.
 - 12" D.Fir bears S.80°W., 26.5 ft. to center scribed S23 BT.
 - 12" D.Fir bears N.20°W., 4.7 ft. to center scribed S14 BT.
- Corner falls 4.5 ft. N.23°W., of fence corner.

BLM dependent resurvey by Wayne Rogers & Bryan Seibold Cadastral Surveyors & Robert Browning, Surveying Technician, under Group #1814, surveyed Aug. 1996/April 1998 - (DCSO rec. Vol. 53 Page(s) 20405-6)

-
- The cor. of secs. 13, 14, 23 and 24, determined at record dist. from the remains of the original NE. and SE. bearing trees, from which the remains of the original bearing trees
- A decayed fir snag, 73" diam., bears N.12½°E., 78 lks., no marks visible on decayed remains. (Record, N.9½°E.)
 - A sawed decayed fir stump, 36" diam., bears S.69°E., 108 lks., with scribe marks S24 T21 R5W BT and a chaining notch visible on open heart wood. (Record, S.72°E.)
 - A decayed fir stump, 30" diam., bears N.74 3/4°W., 82 lks. no marks visible. (Record, N.74°W., 86 lks.)
- At the corner point
- Set a stainless steel post, 28" long, 2½" diam., 26" in the ground, with brass cap mkd.
- continued next page

PRIMARY CORNER DESCRIPTION Sec. Cor. for 13, 14, 23 and 24

Alias	Description
Alias	Description
Alias	Description
Alias	Description

T21S R5W
S 14|S 13
S 23|S 24
1996

from which new bearing trees

- A fir, 23" diam., bears N.67°E., 28 lks., mkd. T21S R5W S13 BT.
- A fir, 32" diam., bears S. 60½° E., 17 lks., mkd. T21S R5W S24 BT.
- A fir, 14" diam., bears S.53°W., 32½ lks., mkd. T21S R5W S23 BT.
- A fir, 11" dia. bears N.33°W. 34 lks. mkd. T21S R5W S14 BT

Deposit a magnet in a white plastic case at the base of the stainless steel post.

From this point, a point erroneously established as the cor. of secs. 13, 14, 23 and 24 by Peterson, in 1977,, bears N.89°28'02"E., 2.746 chs., monumented with an iron pipe, 1" dia., firmly set, projecting 1" above ground, from which a bearing tree used as an original by Peterson

- A fir, 80" diam., bears S.66°E., 108 lks. no marks visible. and bearing trees mkd. by Peterson
- A fir, 15" dia., bears N.61¼°E., 56 lks., with healed blaze.
- A fir, 19" dia., bears S.54°E., 31 lks., with healed blaze.
- A fir, 15" dia., bears S.77°W., 31 lks., with healed blaze
- A fir, 19" dia., bears N.20°W., 7 lks., with healed blaze.