

TOWNSHIP 21 RANGE 05 POINT IDENTIFIER # 600700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1 & 2; 35 & 36, T20-5

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by Harvey Gordon, Deputy Surveyor, Under Contract #49, dated Oct. 17, 1854 - (DCSO records Vol. 2 Page(s) 783)

Set post cor. of secs. 1, 2, 35 and 36, from which
A R.Fir 14" dia., bears N.65°W., 6 lks. dist.
A R.Fir 12" dia., bears N.70°E., 30 lks. dist.
A R.Fir 12" dia., bears S.65°E., 13 lks. dist.
A R.Fir 12" dia., bears S.58°W., 19 lks. dist.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew
Sept. 1965 - C.S. File 54/14-14A

Looked for, not found.

BLM Resurvey by Floyd A. Brooks and Timothy A. Kent, Cadastral Surveyors, under Group #648, Surveyed Aug. 1967/Sept. 1971 - (DCSO records Vol. 37 Page(s) 15256)

Point for the sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28" long, 2 1/2" dia., 22" in the ground, with brass cap mkd:

T 20 S R 5 W
S 35 | S 36
S 2 | S 1
T 21 S
1968

from which

A Fir 15" dia., bears N.33°E., 27 lks. dist., mkd. T20S R5W S36 BT.
A Fir 10" dia., bears S.52°E., 28 lks. dist. mkd. T21S R5W S1 BT.
A Fir 11" dia., bears S.54½°W., 17 lks. dist. mkd. T21S R5W S2 BT.
A Fir 8" dia., bears N.27°W., 24 lks. dist. mkd. T20S R5W S35 BT.

Note this is on the Douglas & Lane Co. line - check with Lane Co for more corner information.