

TOWNSHIP 21 RANGE 05 POINT IDENTIFIER # 640100

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 36; and 1 of T22-5

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 2 Page(s) 790)

Set ¼ sec. post, from which
A Fir 8" dia., bears N.10°E., 100 lks.
A Fir 10" dia., bears S.52°E., 171 lks.

B.H. McGillicuddy - Wit: Marvin; Yoder; Martin and Olson - July 1953 - C.S. File 41/182

Original BTs:
10" Fir now 52", S.52°E., 171 lks. scribed ¼ S BT.
8" Fir now 44", N.10°E., 100 lks., not examined.
New BT - 15" Fir S.24°W., 79.6 ft.

Survey by Bruce A. Shaner - For: U.S. BLM - Aug. 30, 1972 - M 42-68

Found - 1" Iron pipe set in ground and a partially rotted 4" x 4" Post mkd. "¼ S" with scribing visible laying beside the iron pipe.
Orig. D.Fir, now 56", bears N.8°E., 68.4 ft. (Rec. N.10°E., 66.0 ft.)
Orig. 62" D.Fir, scribes visible, bears S.52°E., 115.0 ft. (Rec. 112.0 ft.)
20" D.Fir BT, bears S.24°W., 80.5 ft. (Rec. 79.6 ft.)
Set Brass cap mkd: T21S T22S R5W W.M. ¼ S S36 S1 1972.

Found OK by Les Roberts, April 2000 - M134-66

DCSO-GIS Corner visitation - 10/13/2005 - Typed: 1/19/2011 - C.S. File 67/33-1

Monument - 1¼" IP w/BC. Comment - 3 live BTs