

TOWNSHIP 21 RANGE 05 POINT IDENTIFIER # 640200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 25 and 36

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Harvey Gordon and Charles T. Gardner, Deputy Surveyors, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 2 Page(s) 794)

-----

Set ¼ sec. post, from which  
A Fir 15" dia., bears S.10°W., 25 lks. dist.  
A Fir 10" dia., bears N.19°E., 47 lks. dist.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - Stone and Stoffel - Dec. 9, 1964 - C.S. File 49/68-58

-----

Looked for, not found.

Survey by Les Roberts - Oct. 1990 - C.S. File 63/104-30

-----

Found - 18" Fir stump S.10°W., 16.5 ft., scribing ¼S visible.  
1855 orig. BT, NE. BT could not be found.  
Set 5/8" x 30" I.R. with cap mkd: "Roberts PLS 1039".  
New BTs- 13" Fir N.49°W., 42.9 ft. scribed/painted red.  
24" Fir N.86½°E., 24.1 ft. scribed/painted red.

BLM dependent resurvey by Wayne Rogers & Bryan Seibold Cadastral Surveyors & Robert Browning, Surveying Technician, under Group #1814, surveyed Aug. 1996/April 1998 - (DCSO rec. Vol. 53 Page(s) 20393)

-----

The ¼ sec. cor. of secs. 25 & 36, perpetuated by Godfrey, in 1964, further perpetuated by Roberts, in 1990, monumented with an iron rod, 5/8" diam., firmly set, projecting 5", above ground, with yellow plastic cap mkd. ROBERTS PLS 1039, from which the remains of an original bearing tree  
A sawed fir stump, 20" diam., bears S.10°W., 25 lks., with scribe marks 1/4S visible on open blaze.  
and the remains of bearing trees mkd. by Roberts  
A sawed fir stump, 24" diam., bears N.86½°E., 35 lks., with scribe marks S1/4 S25 ST visible on open double blazes.  
A fir, 16" diam., bears N.50¼°W., 56 lks., with healed double blazes.

At the corner point  
Set a stainless steel post, 28", long, 2½" diam., 26" in the ground, directly over the iron rod, with brass cap mkd.

T 21 S R 5 W  
¼  $\frac{S 25}{S 36}$   
1997

continued next page

TOWNSHIP 21 RANGE 05 POINT IDENTIFIER # 640200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 25 and 36

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which a new bearing tree  
A fir, 11" diam., bears S.15½°E., 45½ lks., mkd. ¼ S36 BT.  
Deposit a magnet in a white plastic case at the base of the  
stainless steel post.  
Cor. is located E., 0.25 chs. dist. from a course S.20°W.

Found 1997 BLM BC by D. Bentz, Jan. 1998 - 1998-0023A&B  
Found OK by Les Roberts, April 2000 - M134-66