

TOWNSHIP 21 RANGE 05 POINT IDENTIFIER # 640300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 24 and 25

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Harvey Gordon and Charles T. Gardner, Deputy Surveyors, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 2 Page(s) 795-96)

Set ¼ sec. post, from which
A Fir 4" dia., bears S.54°E., 96 lks. dist.
A Maple 2" dia., bears N.12°W., 37 lks. dist.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - Stone and Stoffel, crew - Dec. 9, 1964 - C.S. File 49/68-58

Looked for, not found.

Survey by Jim S. Peterson - For: Doug Smith - June 1977 (Filed Oct. 26, 1977) - M 65-47

Set corner at proportionate distance between SE corner Sec. 24 and top of ridge.
Set ¾" Iron pipe, from which
8" D.Fir bears N.80°E., 9.0 ft. to center, scribed ¼ S24 BT.
6" D.Fir bears S.31°W., 3.4 ft. to center, scribed ¼ S25 BT.

BLM dependent resurvey by Wayne Rogers & Bryan Seibold Cadastral Surveyors & Robert Browning, Surveying Technician, under Group #1814, surveyed Aug. 1996/April 1998 - (DCSO rec. Vol. 53 Page(s) 20398-9)

The ¼ sec. cor. of secs. 24 & 25, reestablished by proportionate measurement by Peterson, in 1977. There is no remaining evidence of the original corner, therefore, this position is accepted as the cor.; monumented with an iron pipe, 1" diam., firmly set, projecting 1" above ground, from which bearing trees mkd. by Peterson

A fir, 17" dia. bears N.80°E., 15½ lks. with healed blaze.

A fir, 11" dia. bears S.31°W., 5 lks., with healed blaze.

At the corner point

Set a stainless steel post, 28", long, 2½" diam., 26" in the ground, directly over the iron pipe, with brass cap mkd.

T 21 S R 5 W
S 24
¼ S 25
1997

Deposit a magnet in a white plastic case at the base of the stainless steel post.