

TOWNSHIP 21 RANGE 05 POINT IDENTIFIER # 640500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 12 & 13

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Harvey Gordon and Charles T. Gardner, Deputy Surveyors, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 2 Page(s) 798)

Set ¼ sec. post, from which
A Fir 40" dia., bears N.46°E., 70 lks. dist.
A Fir 36" dia., bears S.63°W., 154 lks. dist.

O.F. Thiel - For: Pioneer Lumber Co. - April 1928 - F.B. 116 Page 31

Set a Fir post. Remarkd both old trees.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - Vernon Tracy; Clete Putnam, crew - Jan. 1962 - C.S. File 49/89-44

Found - Rotted Fir stump 66", N.46°E., 46.2 ft., barely visible old bark scribing "¼S BT".
Stump hole with fragments of rotted Fir roots and part of stump, S.63°W., 101.6 ft. Too far gone to find scribing or axe marks.
Rotted Fir stump, S.38°W., 15.5 ft., scribing visible "BT", not orig. BT, scribing looks like Thiel's.

Set Brass cap at cor. mkd: County Surveyors Office
T 21 S R 5 W
¼ S 12
S 13
1962

New BTs- 8" D.Fir S.50½°W., 20.0 ft. mkd. ¼ S13 CS BT.
19" D.Fir N.36°W., 29.8 ft. mkd. ¼ S12 CS BT.

Fd. OK, June 1990 - M 110-25

BLM dependent resurvey by Wayne Rogers & Bryan Seibold Cadastral Surveyors & Robert Browning, Surveying Technician, under Group #1814, surveyed Aug. 1996/April 1998 - (DCSO rec. Vol. 53 Page(s) 20417-8)

The 1/4 sec. cor. of secs. 12 and 13, perpetuated by Godfrey, in 1962, monumented with an iron post, 1½" diam., firmly set, projecting 10" above ground, with properly brass cap, from which the remains of an original bearing tree

A sawed decayed fir stump, 44" diam., bears N.46°E., 70 lks., no marks visible.
continued next page

TOWNSHIP 21 RANGE 05 POINT IDENTIFIER # 640500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 12 & 13

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

and the remains of bearing trees mkd. by Godfrey
A fir, 20" diam., bears S.50½°W., 30½ lks., with healed double blazes.
A sawed fir stump, 31" diam., bears N.36°W., 43½ lks., with healed double blazes.
and a new bearing tree
A fir, 8" diam., bears N.33°E., 123 lks., mkd. ¼ S12 BT.
The cor. is located S., 0.70 chs. from a small creek, course S.35°E.
From this same point, the BLM, Geodetic Control Station No. EC41250, at latitude 43°45'06.195"N., longitude 123°14'38.899"W., (NAD 1983 (91)), determined by the NAVSTAR Global Positioning System, bears N.76°24'36"W., 26.424 chs. (mean bearing and sea level distance), monumented with an aluminum cap, firmly set flush with the ground, with top mkd. GPS EC41250 1996.