

TOWNSHIP 21 RANGE 05 POINT IDENTIFIER # 640600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 1 and 12

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Harvey Gordon and Charles T. Gardner, Deputy Surveyors, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 2 Page(s) 799)

Set ¼ sec. post, from which
A Fir 36" dia., bears S.6°E., 12 lks. dist.
A Fir 30" dia., bears N.70°W., 9 lks. dist.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - Vernon Tracy; Clete Putnam, crew - Jan. 1962 - C.S. File 49/89-42

Found - Scribed wooden stake at corner.
Old Fir stump S.6°E., 7.9 ft., found bark scribing
"¼ BT"

Set Brass cap at cor. mkd: County Surveyors Office
T 21 S R 5 W
¼ $\frac{S}{S} \frac{1}{12}$
1962

New BTs- 10" D.Fir S.64½°W., 22.3 ft. mkd. ¼ S12 CS BT.
12" D.Fir N.1°W., 21.4 ft. mkd. ¼ S1 CS BT.

Les Roberts, LS #1039 - For: Seneca Timber - June 1990 - M 110-25

CORNER REPORT ONLY

Found - 1962 DCSO brass cap.
42" Fir stump N.70°W., 6.9 ft., no marks. 1854 BT.
(Not found in previous renewal)
48" Fir stump, S.07°E., 9.3 ft., bark scribe. 1854
20" Fir S.65°W., 22.2 ft., scar visible. 1962 BT.
24" Fir, N.01°W., 20.8 ft., scar visible. 1962 BT.