

TOWNSHIP 21 RANGE 05 POINT IDENTIFIER # 700100

PRIMARY CORNER DESCRIPTION SE Tsp. Cor. (SE Cor. Sec. 36)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 2 Page(s) 790)

Set Post cor. of Tp. 21 and 22 S., Rs. 4 and 5 W., from which
A Fir 40" dia., bears S.14°W., 200 lks. dist.
A Fir 60" dia., bears N.43°W., 109 lks. dist.
A Fir 20" dia., bears N.34½°E., 187 lks. dist.
A Fir 15" dia., bears S.13 3/4°E., 369 lks. dist.

0.F. Thiel - For: Yoncalla Lumber Co. - May 1948 - Field Book #5 Page 18

Old bearing trees fallen. Fence post set by survey for S.S. Thomas in 1912. (Cor. of wire fence)

B.H. McGillicuddy - Wit: Marvin Deeds; Francis Yoder; Leo Martin; Vern Olson - July 1953 - C.S. File 41/182

Found - 40" Fir, burned stub, S.11°30'W., 200 lks.
Orig. S14°W., old scribed post. BTs destroyed.
Set 3/4" I.Pipe and scribed new BTs:
24" Fir N.42°30'E., 26.4 ft. mkd. T21S R4W S31 BT
28" Fir N.9°30'W., 51.7 ft. mkd. T21S R5W S36 BT
28" Fir S.21°10'W., 60.7 ft. mkd. T22S R5W S1 BT
26" Fir S.25°30'E., 5.0 ft. mkd. T22S R4W S6 BT

Fd. Corner set by McGillicuddy, Oct. 1964, M.E. Godfrey, DCSO, C.S. File 49/68-21

Survey by Bruce A. Shaner - For: U.S. BLM - Aug. 30, 1972 - M 42-68

Found - 3/4" I.Pipe and 4' x 4" Post with scribing visible, laying beside the I.P.
30" D.Fir BT, face visible, bears S.25½°E., 6.0 ft. (Rec. 5.0 ft.)
34" D.Fir BT, face visible, bears N.42½°E., 27.8 ft. (Rec. 26.4 ft.)
34" D.Fir BT, face visible, bears N.9½°W., 52.5 ft. (Rec. 51.7 ft.)
28" D.Fir BT, scribes visible, bears S.21¼°W., 60.7 ft.
40" Orig. D.Fir BT, burned stub, bears S.11½°W., 132.0 ft.
Set Brass cap mkd: T21S R5W R4W S36 S31 S1 S6 1972.

(Cont. Next Page)

TOWNSHIP 21 RANGE 05 POINT IDENTIFIER # 700100

PRIMARY CORNER DESCRIPTION SE Cor. Sec. 36 (SE Tsp. corner)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Corner found and used in BLM resurvey by Rogers, etal - under Group #1406, surveyed Feb. 1988/Jan. 1989 (DCSO records, Vol. 48 Pages 18601-02)

DCSO-GIS Corner visitation - 5/19/2004 - Typed: 1/12/2011 - C.S. File 67/33-1

Mon Type - BC Size - 1.25"
Comments: OK

David Edwards - For: Seneca Jones Timber Co. - 7/2013 - C.S. file 65/79-11

Found - Brass cap
 44" Fir N.43¼°E., 27.7'
 37" Fir S.25°E., 5.9'
 41" Fir S.20¼°W., 61.4'
 37" Fir stump N.10°W., 52.1'
Set - 6 ft. steel post 2' south